



# Aspen Cloud Server API

## Development Guideline

Defining next generation of cloud based grid  
Myasia Cloud  
(20th October , 2010, version 2.0)

**Table of Content**

Change Log	3
Overview	4
More about Aspen Cloud Server API	5
What skill is required?	6
Terminology	8
Authentication	9
You should know before coding	13
Provided web service API list	14
API 1 – Server List	17
API 2 – Get Server information	19
API 3 – Server Startup	23
API 4 – Server Soft Reboot	25
API 5 – Server Hard Reboot	27
API 6 – Server Soft Shutdown	29
API 7 – Server Hard Shutdown	31
API 8 – Server Subscription	33
API 9 – Server Termination	36
API 10 – Daily Billing Report	38
API 11 – Query supported cities	41
API 12 – Query supported IDC	43
API 13 – Query supported template	45
API 14 – Query template’s plan	48
API 15 – Query extra parts’ plan	50
API 16 – Add extra parts	53
API 17 – Query subscribed parts	55
API 18 – Remove subscribed parts	57
API 19 – Attach SASP-M disk	59
API 20 – Detach SASP-M disk	61
Error Handling	63
Error Code Table	64

Change Log

Changes	Page	Date
“Query extra parts plan” API supported	49	2010-10-19
“Add extra parts” API supported	52	2010-10-19
“Query subscribed parts” API supported	54	2010-10-19
“Remove subscribed parts” API supported	56	2010-10-19
Revise API 12 “Query supported IDC”.	42	2010-10-19
“Attach SASP-M disk” API supported	58	2010-10-19
“Detach SASP-M disk” API supported	60	2010-10-19
Revise API 2 (Get server information)	19	2010-10-19
Support “Super user” mode for “Cloud Server Subscription”.	30	2010-07-12
Cloud Server subscription API supported	32	2010-06-23
Cloud Server termination API supported	35	2010-06-23
“Daily Billing” API supported	37	2010-06-23
“Query city” API supported	40	2010-06-23
“Query IDC” API supported	42	2010-06-23
“Query template” API supported	44	2010-06-23
“Query template’s plan” API supported	49	2010-06-23
Enhance the XML result for function, “Server List” and “Get Server Information”	17, 19	2010-03-17
Detailed description for Cloud Server	19	2010-03-17



## Overview

Aspen Cloud Server provides cloud computing virtual server to client. You can subscribe your own virtual server via <http://cserver.myasiacloud.com> anytime.

Now we further provide API to each user for own development of program and integrate to existing system.

All APIs are RESTful web service call which are platform independent and for fast development. Even you are JAVA, Microsoft .NET, or PHP developer, you can easy to develop without obstacle.

More about Aspen Cloud Server API

Q : Why and who need API ?

A : If you don't want to control the subscribed Cloud Server via our control panel, you can use our RESTful API to control.

You can integrate these Cloud Server functions to your existing system.

Q : What functions provided by Cloud Server API now?

A : Now only Control Panel functions are provided in API.

	API Name	Description
1	Server list	Show all subscribed Cloud Server in XML format.
2	Get server information	Show a specified Cloud Server in details.
3	Server startup	Boot up a specified Cloud Server.
4	Server soft reboot	Soft reboot a specified Cloud Server.
5	Server hard reboot	Hard reboot a specified Cloud Server.
6	Server soft shutdown	Soft shutdown a specified Cloud Server.
7	Server hard shutdown	Hard shutdown a specified Cloud Server.
8	New server subscription	Subscribe new cloud server
9	Server termination	Terminate a subscribed cloud server.
10	Get billing	Get daily billing records for specified date range.
11	Query supported cities	Show which city supports cloud server
12	Query supported IDC	Show which data center supports cloud server in a city or specified service (e.g. SASP-M).
13	Query supported templates	Show what templates are available in specified city. It includes "Standard", "Custom" templates and "Zone".
14	Query template plan	Show all plan for specified template.
15	Query extra parts plan	Show extra parts' price plan. e.g. CPU/RAM
16	Add extra parts	Add extra parts to specified server or IDC.
17	Query subscribed parts	Show what parts are subscribed.
18	Remove subscribed parts	Remove subscribed extra parts from server or IDC.
19	Attach SASP-M disk	Attach SASP-M disk to specified server.
20	Detach SASP-M disk	Detach SASP-M disk from specified server.

## What skill is required ?

Before starting, everyone will ask a question, “what’s skill I should know for calling Aspen Cloud Server API”? To a programmer, this question is more important than pricing. Aspen Cloud Server API provides the world-wide popular method and powerful method. i.e. REST. All provided web services are in RESTful.

Nowadays, REST is a hot web service method because of its flexible and easy to understand. REST is similar to browse a web page via http URL only. In browser, you always utilize the GET method in HTTP to browse web page. In rest, we will take advantages of other HTTP methods such as PUT, DELETE and so on. You can visit [http://en.wikipedia.org/wiki/Representational\\_State\\_Transfer](http://en.wikipedia.org/wiki/Representational_State_Transfer) for details understand of REST.

It is program independent function call so different developer can develop own program base on his/her favorite programming platform and language. Web service call uses http protocol (port 80) to communicate so it can reduce the trouble made by firewall. Besides, all result queries are in XML format.

Even you are a newbie in web service. We can sure you can understand how to start your first step via this development guideline.

## What skills required?

- Basic XML knowledge
- Basic knowledge of web services especially in REST.



### Which programming language platform supported?

The advantage of Aspen Cloud Server API is platform and language independent so you can use what language you like. Main point is that your language can call web services. In general, following language can call our services.

- Java
- PHP
- .Net including C# and VB.Net
- Python
- C++
- Perl
- Ruby
- Even some old language such as Visual Basic v6.0

### What software required?

If programming language support general XML handling functions and http access functions (Best have specified REST call modules), then you can use Aspen Cloud Server API more easily. No any installation or add-on software is required.

## Terminology and Cloud Server Status

### Terminology

Terms	Description
<b>1. Access ID</b>	It is a global unique ID for each user a/c. It is system generated and can't be changed. Once user registers in portal, it will be generated.
<b>2. Secret Access Key</b>	It is a global unique key for signature generation. This key is secret except of owner. Don't share this key to other people. Use this key to generate resource signature for authorization.
<b>3. Server ID</b>	It is a global unique label of your subscribed server which is generated by system.
<b>4. Locale</b>	It is used to control the output language of xml. It includes general output and error message. Now we support English (en), Traditional Chinese (zh_TW) and Simplified Chinese (zh_CN).
<b>5. REST Http Method</b>	In Aspen Cloud Server, some http methods are supported. i.e. <b>POST, GET</b>
<b>6. Parts Code</b>	It is used to represent a parts. You can use the "parts code" to subscribe the parts.
<b>7. Parts ID</b>	After subscribe an extra parts, an unique "parts id" will be assigned to such parts. You can further handle the parts via "parts id".
<b>8. Service type</b>	It is used to identify what parts / service you specify in API. This is a constant value. Now only support <b>cpu, ram, saspm6</b> and <b>saspm</b> .

### Cloud Server Status

Each subscribed cloud server has a status. You can get it via API 1 and 2 but this status may not real time show your server status because you can manual change server. Not by Control Panel.

Terms	Description
<b>PO</b>	Power off
<b>S</b>	Standby i.e. your cloud server is booted up.
<b>R</b>	Rebooting. If your server is be rebooting. Don't try to run other process on it. It will cause error.
<b>U</b>	Undfined/Unclassify – Sometimes the server status can't be get well. If you get this status, you can retry after a while.

## Authentication

Each request should be authenticated. Aspen Cloud Server API uses signature to identify the access user. The signature is composed in client side (i.e. your developed program) and then sends via http header “Authorization”. It is the standard http header. For security issue, most provided functions require user to provide “Access Proof” when access the resource. A valid signature is a proof.

After Aspen Cloud Server API side received the web service request from client. It will check the incoming header whether has “Authorization”.

### Example:

The http header should be similar to following. From following example, the header “Authorization” is specified in header. The format is “access id + signature”.


```
GET / HTTP/1.1
Host: a.cserver.mygrid.asia
Date: Wed, 01 Mar 2006 12:00:00 GMT
(or “x-pan-date” instead of “Date” because some language (e.g. C#) don’t let user to edit “Date”)
```

### Formula of Authorization header

```
Authorization = access ID + colon + signature
(e.g. Authorization: 0000001:dskfjdsklfjkdsljfk9890dsffsdsf)
```

The access ID is given to user after he/she registers. The signature is generated by developer who wants to access Aspen Cloud Server API. Without “Authorization”, Aspen Cloud Server API must reject your request. Thus, developer must understand how to create a signature.

The signature is composed of date time, access api and user secret key. The access id and user secret key are global unique. After Aspen Cloud side receives the submitted http header information. Aspen Cloud will try to generate an identical signature by the provided information such as header time, host, and api and so on. Then compare the system generated signature to user provided signature. If same, that's mean the user is authenticated and vice versa.



The generated signature will be expired after 15 minutes for security issue.

Three steps to generate signature.

### Step 1. Form “request content base”

```
Request Content Base = "<" + HTTP Action (PUT, GET, POST, or DELETE) + ">" +  
                      "<" + current date time (Use RFC 2822 format) + ">" +  
                      "<" + Access ID + ">" +  
                      "<" + API Name + ">" +  
                      "<" + Server ID + ">" (Optional. Server ID is depended on API)
```

#### Explanation:

HTTP Action is PUT or GET or DELETE or POST of your web service request. It is string. The date format is in RFC 2822 format e.g. Thu, 21 Dec 2000 16:01:07 +0800. If your API is no server ID, no need to use server ID.

“Server ID” is not a must. Depends on what API you call. If your API is not related to server, no need to assign “server ID”.

### Step 2 Generate a signature

Every registered member has a “Secret Access Key”. Use it as a key and use algorithm HMAC-SHA1 to encode the “Request Content Base”. Then, use Base64 to encode the output signature. It makes the signature is ASCII string and for header data passing.

1. Incomplete Signature=HMAC-SHA1 (Request Content Base, User Secret Key)
2. Signature =Base64 (Incomplete Signature)



### Step 3 Form the http authentication header

There is no “Authentication” in standard http so we only utilize the other attribute “Authorization”. Now, you have a signature and Access ID. You only concatenate together.

```
Authorization: 0000001:dskfjdsklfjdkslfkd9890dsffdsf
```

Pass above “authorization” in header to Cloud Server API side.

## You should know before coding

1. Before using API, you must register in <http://cserver.myasiacloud.com/>. After you register, you can login and get the Access ID and Secret Access Key for authorization.
2. Adopt RFC2822 (<http://www.faqs.org/rfcs/rfc2822>) date format. e.g. Fri, 30 May 2008 12:00:00 GMT (Greenwich) or Fri, 30 May 2008 08:00:00 +0800 (Hong Kong and China time zone) Both refer to same time.  
“day of week” and “second” are optional. Date and time is local date time. Time zone is the difference from UT/GMT.
3. Most web services request a signature to identify the user. Each signature will be expired after 15 minutes.
4. In each request, user should send header “Date” to Aspen Cloud. For example, pass “Date: Sun, 27 Jul 2008 15:25:16 +0800”. However, some programming language such as C# protects the standard http header field including “Date”. Thus, user can’t assign “Date” directly via C#. Aspen Cloud also provides other http header to replace “Date”. i.e. x-pan-date. If both “Date” and “x-pan-date” are passed to Aspen Cloud Server API. The “x-pan-date” has higher priority than “Date”.

Provided web service API list

	API Name	Description	HTTP
1	Server list	Show all subscribed Cloud Server in XML format. e.g. <a href="http://a.cserver.mygrid.asia/server_list/locale/en">http://a.cserver.mygrid.asia/server_list/locale/en</a>	GET
2	Get server information	Show a specified Cloud Server in details. e.g. <a href="http://a.cserver.mygrid.asia/get_server_info/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/get_server_info/serverid/abcde/locale/en</a> (General mode) or <a href="http://a.cserver.mygrid.asia/get_server_info/serverid/abcde/locale/en/admin_mode">http://a.cserver.mygrid.asia/get_server_info/serverid/abcde/locale/en/admin_mode</a> (Administrator mode)	GET
3	Server startup	Boot up a specified Cloud Server. e.g. <a href="http://a.cserver.mygrid.asia/startup/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/startup/serverid/abcde/locale/en</a>	POST
4	Server soft reboot	Soft reboot a specified Cloud Server. e.g. <a href="http://a.cserver.mygrid.asia/soft_reboot/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/soft_reboot/serverid/abcde/locale/en</a>	POST
5	Server hard reboot	Hard reboot a specified Cloud Server. e.g. <a href="http://a.cserver.mygrid.asia/hard_reboot/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/hard_reboot/serverid/abcde/locale/en</a>	POST
6	Server soft shutdown	Soft shutdown a specified Cloud Server. e.g. <a href="http://a.cserver.mygrid.asia/soft_shutdown/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/soft_shutdown/serverid/abcde/locale/en</a>	POST
7	Server hard shutdown	Hard shutdown a specified Cloud Server. e.g. <a href="http://a.cserver.mygrid.asia/hard_shutdown/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/hard_shutdown/serverid/abcde/locale/en</a>	POST
8	Server subscription	Subscribe a new cloud server e.g. (with zone) <a href="http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%2/plan_code/5Dq%26g/zone_code/Spc3xH%60mKOquk">http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%2/plan_code/5Dq%26g/zone_code/Spc3xH%60mKOquk</a>	PUT

		<p>or (without zone)</p> <p><a href="http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%2Fplan_code/5Dq%26g">http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%2Fplan_code/5Dq%26g</a></p>	
9	Server termination	<p>Terminate a subscribed cloud server</p> <p>e.g.</p> <p><a href="http://a.cserver.mygrid.asia/server_terminate/serverid/111111/locale/en">http://a.cserver.mygrid.asia/server_terminate/serverid/111111/locale/en</a></p>	DELETE
10	Daily billing	<p>Get daily billing record</p> <p>e.g.</p> <p><a href="http://a.cserver.mygrid.asia/daily_billing_report/locale/en/start_date/2010-06-21/end_date/2010-06-30/offset/1/max/10">http://a.cserver.mygrid.asia/daily_billing_report/locale/en/start_date/2010-06-21/end_date/2010-06-30/offset/1/max/10</a></p>	GET
11	Query supported cities	<p>Show which city supports cloud server</p> <p>e.g.</p> <p><a href="http://a.cserver.mygrid.asia/query_support_city/locale/en">http://a.cserver.mygrid.asia/query_support_city/locale/en</a></p>	GET
12	Query supported IDC	<p>Show which data center supports cloud server in a city.</p> <p>2 formats supported e.g.</p> <p><a href="http://a.cserver.mygrid.asia/query_support_idc/locale/en/citycode/nQ%40%3B">http://a.cserver.mygrid.asia/query_support_idc/locale/en/citycode/nQ%40%3B</a></p> <p>or,</p> <p><a href="http://a.cserver.mygrid.asia/query_support_idc/locale/en/service_type/saspm">http://a.cserver.mygrid.asia/query_support_idc/locale/en/service_type/saspm</a></p>	GET
13	Query supported templates	<p>Show what templates are available in specified city.</p> <p>It includes “Standard”, “Custom” templates and “Zone”.</p> <p>e.g.</p> <p><a href="http://a.cserver.mygrid.asia/query_support_template/locale/en/idc_code/nQ%40%3B">http://a.cserver.mygrid.asia/query_support_template/locale/en/idc_code/nQ%40%3B</a></p>	GET
14	Query template plan	<p>Show all plans for specified template.</p> <p>e.g.</p> <p><a href="http://a.cserver.mygrid.asia/query_template_price/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F.%5Dq%26g">http://a.cserver.mygrid.asia/query_template_price/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F.%5Dq%26g</a></p>	GET
15	Query extra parts plan	<p>Show extra parts’ price plan. e.g. CPU/RAM/SASP-6/SASP-M</p> <p>2 formats supported.</p> <p>e.g.</p> <p><a href="http://a.cserver.mygrid.asia/query_extra_parts_plan/locale/en/serverid/111111/service_type/cpu">http://a.cserver.mygrid.asia/query_extra_parts_plan/locale/en/serverid/111111/service_type/cpu</a></p> <p>or</p>	GET

		<a href="http://a.cserver.mygrid.asia/query_extra_parts_plan/locale/en/idc_code/111/service_type/saspm">http://a.cserver.mygrid.asia/query_extra_parts_plan/locale/en/idc_code/111/service_type/saspm</a>	
16	Add extra parts	<p>Add extra parts to specified server or IDC. 2 formats supported e.g. <a href="http://a.cserver.mygrid.asia/add_extra_parts/locale/en/serverid/11111/service_type/ram/parts_code/xyz">http://a.cserver.mygrid.asia/add_extra_parts/locale/en/serverid/11111/service_type/ram/parts_code/xyz</a> or <a href="http://a.cserver.mygrid.asia/add_extra_parts/locale/en/idc_code/00001/service_type/saspm/parts_code/xyz">http://a.cserver.mygrid.asia/add_extra_parts/locale/en/idc_code/00001/service_type/saspm/parts_code/xyz</a></p>	PUT
17	Query subscribed parts	<p>Show what parts are subscribed. e.g. <a href="http://a.cserver.mygrid.asia/query_extra_subscribed_service/locale/en/service_type/cpu">http://a.cserver.mygrid.asia/query_extra_subscribed_service/locale/en/service_type/cpu</a></p>	GET
18	Remove subscribed parts	<p>Remove subscribed extra parts from server or IDC. 2 formats supported e.g. <a href="http://a.cserver.mygrid.asia/remove_extra_parts/locale/en/serverid/11111/service_type/cpu/parts_id/abcdef">http://a.cserver.mygrid.asia/remove_extra_parts/locale/en/serverid/11111/service_type/cpu/parts_id/abcdef</a> or <a href="http://a.cserver.mygrid.asia/remove_extra_parts/locale/en/service_type/saspm/parts_id/zyx">http://a.cserver.mygrid.asia/remove_extra_parts/locale/en/service_type/saspm/parts_id/zyx</a></p>	DELETE
19	Attach SASP-M disk	<p>Attach SASP-M disk to specified server. e.g. <a href="http://a.cserver.mygrid.asia/attach_disk/locale/en/serverid/11111/parts_id/abcdefg">http://a.cserver.mygrid.asia/attach_disk/locale/en/serverid/11111/parts_id/abcdefg</a></p>	PUT
20	Detach SASP-M disk	<p>Detach SASP-M disk from specified server. e.g. <a href="http://a.cserver.mygrid.asia/detach_disk/locale/en/serverid/11111/parts_id/abcdefg">http://a.cserver.mygrid.asia/detach_disk/locale/en/serverid/11111/parts_id/abcdefg</a></p>	DELETE

API 1 – Server List

<b>Web Service Name</b>	<b>server_list (ID_1)</b>	<b>REST http method</b>	<b>GET</b>																														
<b>Description</b>	Get the subscribed cloud server list in XML																																
<b>REST example</b>	http://a.cserver.mygrid.asia/server_list/locale/en																																
<b>Http Code if success</b>	200																																
<b>Request Signature</b>	Yes																																
<b>Anonymous access</b>	Not accept																																
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>1. Expired signature</td> <td>ExpiredSig</td> <td>400 Bad Request</td> </tr> <tr> <td>2. Invalid headers</td> <td>InvalidHeader</td> <td>400 Bad Request</td> </tr> <tr> <td>3. Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>4. No such member</td> <td>NotExistMem</td> <td>400 Bad Request</td> </tr> <tr> <td>5. Fail Authentication</td> <td>FailAuth</td> <td>403 Forbidden</td> </tr> <tr> <td>6. Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>7. Unsupported REST action</td> <td>NoRestMethod</td> <td>405 Not allowed method</td> </tr> <tr> <td>8. Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>9. Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	1. Expired signature	ExpiredSig	400 Bad Request	2. Invalid headers	InvalidHeader	400 Bad Request	3. Incorrect Locale code passing	InvalidLocale	400 Bad Request	4. No such member	NotExistMem	400 Bad Request	5. Fail Authentication	FailAuth	403 Forbidden	6. Account problem or suspended	ACPrb	403 Forbidden	7. Unsupported REST action	NoRestMethod	405 Not allowed method	8. Server unexpected error	UnexpectedError	500 Server error	9. Service unavailable	UnavailableService	503 Service Unavailable
Error Description	Error Code	Http Status Code																															
1. Expired signature	ExpiredSig	400 Bad Request																															
2. Invalid headers	InvalidHeader	400 Bad Request																															
3. Incorrect Locale code passing	InvalidLocale	400 Bad Request																															
4. No such member	NotExistMem	400 Bad Request																															
5. Fail Authentication	FailAuth	403 Forbidden																															
6. Account problem or suspended	ACPrb	403 Forbidden																															
7. Unsupported REST action	NoRestMethod	405 Not allowed method																															
8. Server unexpected error	UnexpectedError	500 Server error																															
9. Service unavailable	UnavailableService	503 Service Unavailable																															
<b>REST Request Header</b>	GET / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i>																																

	Authorization: 112122334214:dsfksfjdklsfjklfsjf-dsfd= <i>(access_id : signature)</i>
<b>REST Respond Header if success</b>	<p>HTTP/1.1 200 OK</p> <p>Date: Mon, 03 Mar 2008 12:00:00 GMT</p> <p>Content-Length: 112</p> <p>Connection: close</p> <p>Content-Type: application/xml</p>
<b>REST XML Expected Result</b>	<pre> &lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;SubscribedServer&gt;   &lt;Profile&gt;     &lt;AccessID&gt;dsfsdfCga6Ug8ORWyayE51eQ1ke58sbyaCO&lt;/AccessID&gt;     &lt;LoginName&gt;peterpan&lt;/LoginName&gt;     &lt;NoOfServer&gt;1&lt;/NoOfServer&gt;   &lt;/Profile&gt;   &lt;ServerList&gt;     &lt;Server&gt;       &lt;ServerID&gt;dsfjksdfjksdjfdjfkdsjfkd&lt;/ServerID&gt;       &lt;ServerDescription&gt;first server&lt;/ServerDescription&gt;       &lt;Location&gt;Malaysia&lt;/Location&gt;       &lt;IDC&gt;AIMS IDC&lt;/IDC&gt;       &lt;Plan&gt;Plan A&lt;/Plan&gt;       &lt;OSType&gt;Linux&lt;/OSType&gt;       &lt;OSName&gt;Centos 5.2 (64bit)&lt;/OSName&gt;       &lt;Template&gt; Centos 5.2 (64bit)&lt;/Template&gt;       &lt;DNS&gt;29-h99.my00001.cserver.mygrid.asia&lt;/DNS&gt;       &lt;ServerZone&gt;Zone A&lt;/ServerZone&gt;       &lt;IsSuspended&gt;Y&lt;/Suspended&gt; <b>(Y-YES / N- NO)</b>       &lt;ServerStatusCode&gt;PO&lt;/ServerStatusCode&gt;       &lt;ServerStatusDescription&gt;Poweroff&lt;/ServerStatusDescription&gt;     &lt;/Server&gt;   &lt;/ServerList&gt; &lt;/SubscribedServer&gt; </pre>

## API 2 – Get Server Information

<b>Web Service Name</b>	<b>get_server_info (ID_2)</b>	<b>REST http method</b>	<b>GET</b>																																	
<b>Description</b>	Get the subscribed cloud server list in XML																																			
<b>REST example</b>	2 modes General mode : <a href="http://a.cserver.mygrid.asia/get_server_info/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/get_server_info/serverid/abcde/locale/en</a> or, Administrator mode (for super user only. General user can't use) : <a href="http://a.cserver.mygrid.asia/get_server_info/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/get_server_info/serverid/abcde/locale/en</a>																																			
<b>Http Code if success</b>	200																																			
<b>Request Signature</b>	Yes																																			
<b>Anonymous access</b>	Not accept																																			
<b>Possible Error</b>	<b>General errors</b> <table border="1" data-bbox="422 996 1340 1585"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>1. Expired signature</td> <td>ExpiredSig</td> <td>400 Bad Request</td> </tr> <tr> <td>2. Invalid headers</td> <td>InvalidHeader</td> <td>400 Bad Request</td> </tr> <tr> <td>3. Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>4. No such member</td> <td>NotExistMem</td> <td>400 Bad Request</td> </tr> <tr> <td>5. Fail Authentication</td> <td>FailAuth</td> <td>403 Forbidden</td> </tr> <tr> <td>6. Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>7. No administrator right</td> <td>NoAdminAccessRig ht</td> <td>403 Forbidden</td> </tr> <tr> <td>8. Unsupported REST action</td> <td>NoRestMethod</td> <td>405 Not allowed method</td> </tr> <tr> <td>9. Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>10. Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	1. Expired signature	ExpiredSig	400 Bad Request	2. Invalid headers	InvalidHeader	400 Bad Request	3. Incorrect Locale code passing	InvalidLocale	400 Bad Request	4. No such member	NotExistMem	400 Bad Request	5. Fail Authentication	FailAuth	403 Forbidden	6. Account problem or suspended	ACPrb	403 Forbidden	7. No administrator right	NoAdminAccessRig ht	403 Forbidden	8. Unsupported REST action	NoRestMethod	405 Not allowed method	9. Server unexpected error	UnexpectedError	500 Server error	10. Service unavailable	UnavailableService	503 Service Unavailable
Error Description	Error Code	Http Status Code																																		
1. Expired signature	ExpiredSig	400 Bad Request																																		
2. Invalid headers	InvalidHeader	400 Bad Request																																		
3. Incorrect Locale code passing	InvalidLocale	400 Bad Request																																		
4. No such member	NotExistMem	400 Bad Request																																		
5. Fail Authentication	FailAuth	403 Forbidden																																		
6. Account problem or suspended	ACPrb	403 Forbidden																																		
7. No administrator right	NoAdminAccessRig ht	403 Forbidden																																		
8. Unsupported REST action	NoRestMethod	405 Not allowed method																																		
9. Server unexpected error	UnexpectedError	500 Server error																																		
10. Service unavailable	UnavailableService	503 Service Unavailable																																		
<b>REST Request</b>	GET / HTTP/1.1																																			

<b>Header</b>	<p>Host: a.cserver.mygrid.asia</p> <p>Content-Length: 0</p> <p>Date: Mon, 03 Mar 2008 12:00:00 +0800</p> <p><i>(or passing x-pan-date instead of Date)</i></p> <p>Authorization: 112122334214:dsfdksfjdklsfjklfsfj-dsfd= <i>(access_id : signature)</i></p>
<b>REST Respond Header if success</b>	<p>HTTP/1.1 200 OK</p> <p>Date: Mon, 03 Mar 2008 12:00:00 GMT</p> <p>Content-Length: 112</p> <p>Connection: close</p> <p>Content-Type: application/xml</p>
<b>REST XML Expected Result for “General Mode”.</b>	<pre>&lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;ServerInformation&gt; &lt;Profile&gt;   &lt;AccessID&gt;MUg8ORWyayE51eQ1ke58sbyaCO&lt;/AccessID&gt;   &lt;LoginName&gt;davidchan&lt;/LoginName&gt; &lt;/Profile&gt; &lt;Server&gt;   &lt;ServerID&gt;e80211f0-7aa6-44b5-bc80-ba47f06bb42d&lt;/ServerID&gt;   &lt;ServerDescription&gt;test server&lt;/ServerDescription&gt;   &lt;Group /&gt;   &lt;Zone&gt;Zone A&lt;/Zone&gt;   &lt;DNS&gt;29-h99.my00001.cserver.mygrid.asia&lt;/DNS&gt;   &lt;PublicIP&gt;202.x.x.x &lt;/PublicIP&gt;   &lt;PrivateIP&gt;192.168.10.1&lt;/PrivateIP&gt;   &lt;IsSuspended&gt;N&lt;/IsSuspended&gt;   &lt;ServerStatusCode&gt;PO&lt;/ServerStatusCode&gt;   &lt;ServerStatusDescription&gt;Power Off&lt;/ServerStatusDescription&gt;   &lt;ActivationDate&gt;2010-10-19 GMT&lt;/ActivationDate&gt;   &lt;City&gt;Malaysia&lt;/City&gt;   &lt;IDC&gt;Sapura, Malaysia &lt;/IDC&gt;   &lt;OSType&gt;Linux&lt;/OSType&gt;   &lt;OSName&gt;Centos 5.2 (64bit)&lt;/OSName&gt;   &lt;Template&gt;Centos 5.2 (64bit)&lt;/Template&gt;   &lt;Plan&gt;Plan A&lt;/Plan&gt; &lt;/HardwareConfig&gt;</pre>



```

<Virtual_CPU_NO>2</Virtual_CPU_NO>
<RAM_Size_In_MB>768</RAM_Size_In_MB>
<Local_Disk_Size_In_GB>10</Local_Disk_Size_In_GB>
<SASP_6>
<SASP_6_Drive>
<SASP_6_Parts_ID>645761ab-9f1d-4f1d-86a4-fba26e2b8904</SASP_6_Parts_ID>
<SASP_6_Name>sdf</SASP_6_Name>
<SASP_6_Size_In_GB>50</SASP_6_Size_In_GB>
</SASP_6_Drive>
</SASP_6>
<SASP_M>
<SASP_M_Drive>
<SASP_M_Parts_ID>cc419757-04c2-4db0-bab7-953d07b33c72</SASP_M_Parts_ID>
<SASP_M_Name>sdg</SASP_M_Name>
<SASP_M_Size_In_GB>100</SASP_M_Size_In_GB>
</SASP_M_Drive>
</SASP_M>
</HardwareConfig>
<ExtraHardware>
<ExtraCPUList>
<ExtraCPU>
<CPU_Parts_ID>ff8d5708-3207-4805-8454-916d04b22991</CPU_Parts_ID>
<No_Of_CPU>1</No_Of_CPU>
</ExtraCPU>
</ExtraCPUList>
<ExtraRAMList>
<ExtraRAM>
<RAM_Parts_ID>03ce5b29-53a8-4360-b8ae-7dc045f7e626</RAM_Parts_ID>
<RAM_Size>256</RAM_Size>
</ExtraRAM>
<ExtraRAM>
<RAM_Parts_ID>d30f653e-cefa-4a69-ab52-ac5ac0775550</RAM_Parts_ID>
<RAM_Size>256</RAM_Size>
</ExtraRAM>
</ExtraRAMList>
</ExtraHardware>

```

	<pre>&lt;/Server&gt; &lt;/ServerInformation&gt;</pre>
<p><b>REST XML Expected Result for “Administrator Mode”.</b></p>	<pre>&lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;ServerInformation&gt;   &lt;ServerID&gt;e812324f0-7aa6-44b5-bc80-ba47f06bb42d&lt;/ServerID&gt;   &lt;IsSuspended&gt;N&lt;/IsSuspended&gt;   &lt;IsReserved&gt;N&lt;/IsReserved&gt;   &lt;IsLocked&gt;N&lt;/IsLocked&gt;   &lt;IsTerminated&gt;N&lt;/IsTerminated&gt;   &lt;ServerStatusCode&gt;PO&lt;/ServerStatusCode&gt;   &lt;IsSubscribed&gt;Y&lt;/IsSubscribed&gt;   &lt;HasVG&gt;Y&lt;/HasVG&gt;   &lt;AccessID&gt;MUg8ORWyayE51eQ1ke58sbyaCO&lt;/AccessID&gt; &lt;/ServerInformation&gt;</pre>

API 3 – Server Startup

<b>Web Service Name</b>	<b>Startup (ID_3)</b>	<b>REST http method</b>	<b>POST</b>																																							
<b>Description</b>	Boot up a specified server																																									
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/startup/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/startup/serverid/abcde/locale/en</a>																																									
<b>Http Code if success</b>	200																																									
<b>Request Signature</b>	Yes																																									
<b>Anonymous access</b>	Not accept																																									
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>1. Expired signature</td> <td>ExpiredSig</td> <td>400 Bad Request</td> </tr> <tr> <td>2. Invalid headers</td> <td>InvalidHeader</td> <td>400 Bad Request</td> </tr> <tr> <td>3. Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>4. No such member</td> <td>NotExistMem</td> <td>400 Bad Request</td> </tr> <tr> <td>5. No such Cloud Server</td> <td>NoSuchVM</td> <td>400 Bad Request</td> </tr> <tr> <td>6. Fail Authentication</td> <td>FailAuth</td> <td>403 Forbidden</td> </tr> <tr> <td>7. Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>8. The cloud server is locked by other process.</td> <td>VMLocked</td> <td>403 Forbidden</td> </tr> <tr> <td>9. The cloud server was suspended.</td> <td>VMSuspended</td> <td>403 Forbidden</td> </tr> <tr> <td>10. Unsupported REST action</td> <td>NoRestMethod</td> <td>405 Not allowed method</td> </tr> <tr> <td>11. Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>12. Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	1. Expired signature	ExpiredSig	400 Bad Request	2. Invalid headers	InvalidHeader	400 Bad Request	3. Incorrect Locale code passing	InvalidLocale	400 Bad Request	4. No such member	NotExistMem	400 Bad Request	5. No such Cloud Server	NoSuchVM	400 Bad Request	6. Fail Authentication	FailAuth	403 Forbidden	7. Account problem or suspended	ACPrb	403 Forbidden	8. The cloud server is locked by other process.	VMLocked	403 Forbidden	9. The cloud server was suspended.	VMSuspended	403 Forbidden	10. Unsupported REST action	NoRestMethod	405 Not allowed method	11. Server unexpected error	UnexpectedError	500 Server error	12. Service unavailable	UnavailableService	503 Service Unavailable
Error Description	Error Code	Http Status Code																																								
1. Expired signature	ExpiredSig	400 Bad Request																																								
2. Invalid headers	InvalidHeader	400 Bad Request																																								
3. Incorrect Locale code passing	InvalidLocale	400 Bad Request																																								
4. No such member	NotExistMem	400 Bad Request																																								
5. No such Cloud Server	NoSuchVM	400 Bad Request																																								
6. Fail Authentication	FailAuth	403 Forbidden																																								
7. Account problem or suspended	ACPrb	403 Forbidden																																								
8. The cloud server is locked by other process.	VMLocked	403 Forbidden																																								
9. The cloud server was suspended.	VMSuspended	403 Forbidden																																								
10. Unsupported REST action	NoRestMethod	405 Not allowed method																																								
11. Server unexpected error	UnexpectedError	500 Server error																																								
12. Service unavailable	UnavailableService	503 Service Unavailable																																								
<b>REST Request Header</b>	POST / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i>																																									



## Cloud Server API – Development Guideline

	Authorization: 112122334214:dsfdksfjdklsfjklfsfj-dsfd= <i>(access_id : signature)</i>
<b>REST Respond</b> <b>Header if success</b>	HTTP/1.1 200 OK Date: Mon, 03 Mar 2008 12:00:00 GMT Content-Length: 112 Connection: close Content-Type: application/xml
<b>REST XML Expected</b> <b>Result</b>	<?xml version="1.0" encoding="UTF-8" ?> <CloudServerAPI> <Status>SUCCESS</Status> </CloudServerAPI>

## API 4 – Server Soft Reboot

<b>Web Service Name</b>	<b>soft_reboot (ID_4)</b>	<b>REST http method</b>	<b>POST</b>																																							
<b>Description</b>	Soft reboot the cloud server																																									
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/soft_reboot/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/soft_reboot/serverid/abcde/locale/en</a>																																									
<b>Http Code if success</b>	200																																									
<b>Request Signature</b>	Yes																																									
<b>Anonymous access</b>	Not accept																																									
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>1. Expired signature</td> <td>ExpiredSig</td> <td>400 Bad Request</td> </tr> <tr> <td>2. Invalid headers</td> <td>InvalidHeader</td> <td>400 Bad Request</td> </tr> <tr> <td>3. Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>4. No such member</td> <td>NotExistMem</td> <td>400 Bad Request</td> </tr> <tr> <td>5. No such Cloud Server</td> <td>NoSuchVM</td> <td>400 Bad Request</td> </tr> <tr> <td>6. Fail Authentication</td> <td>FailAuth</td> <td>403 Forbidden</td> </tr> <tr> <td>7. Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>8. The cloud server is locked by other process.</td> <td>VMLocked</td> <td>403 Forbidden</td> </tr> <tr> <td>9. The cloud server was suspended.</td> <td>VMSuspended</td> <td>403 Forbidden</td> </tr> <tr> <td>10. Unsupported REST action</td> <td>NoRestMethod</td> <td>405 Not allowed method</td> </tr> <tr> <td>11. Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>12. Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	1. Expired signature	ExpiredSig	400 Bad Request	2. Invalid headers	InvalidHeader	400 Bad Request	3. Incorrect Locale code passing	InvalidLocale	400 Bad Request	4. No such member	NotExistMem	400 Bad Request	5. No such Cloud Server	NoSuchVM	400 Bad Request	6. Fail Authentication	FailAuth	403 Forbidden	7. Account problem or suspended	ACPrb	403 Forbidden	8. The cloud server is locked by other process.	VMLocked	403 Forbidden	9. The cloud server was suspended.	VMSuspended	403 Forbidden	10. Unsupported REST action	NoRestMethod	405 Not allowed method	11. Server unexpected error	UnexpectedError	500 Server error	12. Service unavailable	UnavailableService	503 Service Unavailable
Error Description	Error Code	Http Status Code																																								
1. Expired signature	ExpiredSig	400 Bad Request																																								
2. Invalid headers	InvalidHeader	400 Bad Request																																								
3. Incorrect Locale code passing	InvalidLocale	400 Bad Request																																								
4. No such member	NotExistMem	400 Bad Request																																								
5. No such Cloud Server	NoSuchVM	400 Bad Request																																								
6. Fail Authentication	FailAuth	403 Forbidden																																								
7. Account problem or suspended	ACPrb	403 Forbidden																																								
8. The cloud server is locked by other process.	VMLocked	403 Forbidden																																								
9. The cloud server was suspended.	VMSuspended	403 Forbidden																																								
10. Unsupported REST action	NoRestMethod	405 Not allowed method																																								
11. Server unexpected error	UnexpectedError	500 Server error																																								
12. Service unavailable	UnavailableService	503 Service Unavailable																																								
<b>REST Request Header</b>	POST / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjklfsj-dsfd= <i>(access_id : signature)</i>																																									



<b>REST Respond Header if success</b>	HTTP/1.1 200 OK Date: Mon, 03 Mar 2008 12:00:00 GMT Content-Length: 112 Connection: close Content-Type: application/xml
<b>REST XML Expected Result</b>	<?xml version="1.0" encoding="UTF-8" ?> <CloudServerAPI> <Status>SUCCESS</Status> </CloudServerAPI>

## API 5 – Server Hard Reboot

<b>Web Service Name</b>	<b>hard_reboot (ID_5)</b>	<b>REST http method</b>	<b>POST</b>																																							
<b>Description</b>	Hard reboot the cloud server																																									
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/hard_reboot/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/hard_reboot/serverid/abcde/locale/en</a>																																									
<b>Http Code if success</b>	200																																									
<b>Request Signature</b>	Yes																																									
<b>Anonymous access</b>	Not accept																																									
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>1. Expired signature</td> <td>ExpiredSig</td> <td>400 Bad Request</td> </tr> <tr> <td>2. Invalid headers</td> <td>InvalidHeader</td> <td>400 Bad Request</td> </tr> <tr> <td>3. Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>4. No such member</td> <td>NotExistMem</td> <td>400 Bad Request</td> </tr> <tr> <td>5. No such Cloud Server</td> <td>NoSuchVM</td> <td>400 Bad Request</td> </tr> <tr> <td>6. Fail Authentication</td> <td>FailAuth</td> <td>403 Forbidden</td> </tr> <tr> <td>7. Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>8. The cloud server is locked by other process.</td> <td>VMLocked</td> <td>403 Forbidden</td> </tr> <tr> <td>9. The cloud server was suspended.</td> <td>VMSuspended</td> <td>403 Forbidden</td> </tr> <tr> <td>10. Unsupported REST action</td> <td>NoRestMethod</td> <td>405 Not allowed method</td> </tr> <tr> <td>11. Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>12. Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	1. Expired signature	ExpiredSig	400 Bad Request	2. Invalid headers	InvalidHeader	400 Bad Request	3. Incorrect Locale code passing	InvalidLocale	400 Bad Request	4. No such member	NotExistMem	400 Bad Request	5. No such Cloud Server	NoSuchVM	400 Bad Request	6. Fail Authentication	FailAuth	403 Forbidden	7. Account problem or suspended	ACPrb	403 Forbidden	8. The cloud server is locked by other process.	VMLocked	403 Forbidden	9. The cloud server was suspended.	VMSuspended	403 Forbidden	10. Unsupported REST action	NoRestMethod	405 Not allowed method	11. Server unexpected error	UnexpectedError	500 Server error	12. Service unavailable	UnavailableService	503 Service Unavailable
Error Description	Error Code	Http Status Code																																								
1. Expired signature	ExpiredSig	400 Bad Request																																								
2. Invalid headers	InvalidHeader	400 Bad Request																																								
3. Incorrect Locale code passing	InvalidLocale	400 Bad Request																																								
4. No such member	NotExistMem	400 Bad Request																																								
5. No such Cloud Server	NoSuchVM	400 Bad Request																																								
6. Fail Authentication	FailAuth	403 Forbidden																																								
7. Account problem or suspended	ACPrb	403 Forbidden																																								
8. The cloud server is locked by other process.	VMLocked	403 Forbidden																																								
9. The cloud server was suspended.	VMSuspended	403 Forbidden																																								
10. Unsupported REST action	NoRestMethod	405 Not allowed method																																								
11. Server unexpected error	UnexpectedError	500 Server error																																								
12. Service unavailable	UnavailableService	503 Service Unavailable																																								
<b>REST Request Header</b>	POST / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjkljsfj-dsfd= <i>(access_id : signature)</i>																																									



## Cloud Server API – Development Guideline

<b>REST Respond Header if success</b>	HTTP/1.1 200 OK Date: Mon, 03 Mar 2008 12:00:00 GMT Content-Length: 112 Connection: close Content-Type: application/xml
<b>REST XML Expected Result</b>	<?xml version="1.0" encoding="UTF-8" ?> <CloudServerAPI> <Status>SUCCESS</Status> </CloudServerAPI>

## API 6 – Server Soft Shutdown

<b>Web Service Name</b>	<b>soft_shutdown (ID_6)</b>	<b>REST http method</b>	<b>POST</b>																																							
<b>Description</b>	Soft shutdown the cloud server																																									
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/soft_shutdown/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/soft_shutdown/serverid/abcde/locale/en</a>																																									
<b>Http Code if success</b>	200																																									
<b>Request Signature</b>	Yes																																									
<b>Anonymous access</b>	Not accept																																									
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>1. Expired signature</td> <td>ExpiredSig</td> <td>400 Bad Request</td> </tr> <tr> <td>2. Invalid headers</td> <td>InvalidHeader</td> <td>400 Bad Request</td> </tr> <tr> <td>3. Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>4. No such member</td> <td>NotExistMem</td> <td>400 Bad Request</td> </tr> <tr> <td>5. No such Cloud Server</td> <td>NoSuchVM</td> <td>400 Bad Request</td> </tr> <tr> <td>6. Fail Authentication</td> <td>FailAuth</td> <td>403 Forbidden</td> </tr> <tr> <td>7. Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>8. The cloud server is locked by other process.</td> <td>VMLocked</td> <td>403 Forbidden</td> </tr> <tr> <td>9. The cloud server was suspended.</td> <td>VMSuspended</td> <td>403 Forbidden</td> </tr> <tr> <td>10. Unsupported REST action</td> <td>NoRestMethod</td> <td>405 Not allowed method</td> </tr> <tr> <td>11. Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>12. Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	1. Expired signature	ExpiredSig	400 Bad Request	2. Invalid headers	InvalidHeader	400 Bad Request	3. Incorrect Locale code passing	InvalidLocale	400 Bad Request	4. No such member	NotExistMem	400 Bad Request	5. No such Cloud Server	NoSuchVM	400 Bad Request	6. Fail Authentication	FailAuth	403 Forbidden	7. Account problem or suspended	ACPrb	403 Forbidden	8. The cloud server is locked by other process.	VMLocked	403 Forbidden	9. The cloud server was suspended.	VMSuspended	403 Forbidden	10. Unsupported REST action	NoRestMethod	405 Not allowed method	11. Server unexpected error	UnexpectedError	500 Server error	12. Service unavailable	UnavailableService	503 Service Unavailable
Error Description	Error Code	Http Status Code																																								
1. Expired signature	ExpiredSig	400 Bad Request																																								
2. Invalid headers	InvalidHeader	400 Bad Request																																								
3. Incorrect Locale code passing	InvalidLocale	400 Bad Request																																								
4. No such member	NotExistMem	400 Bad Request																																								
5. No such Cloud Server	NoSuchVM	400 Bad Request																																								
6. Fail Authentication	FailAuth	403 Forbidden																																								
7. Account problem or suspended	ACPrb	403 Forbidden																																								
8. The cloud server is locked by other process.	VMLocked	403 Forbidden																																								
9. The cloud server was suspended.	VMSuspended	403 Forbidden																																								
10. Unsupported REST action	NoRestMethod	405 Not allowed method																																								
11. Server unexpected error	UnexpectedError	500 Server error																																								
12. Service unavailable	UnavailableService	503 Service Unavailable																																								
<b>REST Request Header</b>	POST / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjklfsj-dsfd= <i>(access_id : signature)</i>																																									



<b>REST Respond Header if success</b>	HTTP/1.1 200 OK Date: Mon, 03 Mar 2008 12:00:00 GMT Content-Length: 112 Connection: close Content-Type: application/xml
<b>REST XML Expected Result</b>	<?xml version="1.0" encoding="UTF-8" ?> <CloudServerAPI> <Status>SUCCESS</Status> </CloudServerAPI>

## API 7 – Server Hard Shutdown

<b>Web Service Name</b>	<b>hard_shutdown (ID_7)</b>	<b>REST http method</b>	<b>POST</b>																																							
<b>Description</b>	Hard shutdown the cloud server																																									
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/hard_shutdown/serverid/abcde/locale/en">http://a.cserver.mygrid.asia/hard_shutdown/serverid/abcde/locale/en</a>																																									
<b>Http Code if success</b>	200																																									
<b>Request Signature</b>	Yes																																									
<b>Anonymous access</b>	Not accept																																									
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>1. Expired signature</td> <td>ExpiredSig</td> <td>400 Bad Request</td> </tr> <tr> <td>2. Invalid headers</td> <td>InvalidHeader</td> <td>400 Bad Request</td> </tr> <tr> <td>3. Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>4. No such member</td> <td>NotExistMem</td> <td>400 Bad Request</td> </tr> <tr> <td>5. No such Cloud Server</td> <td>NoSuchVM</td> <td>400 Bad Request</td> </tr> <tr> <td>6. Fail Authentication</td> <td>FailAuth</td> <td>403 Forbidden</td> </tr> <tr> <td>7. Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>8. The cloud server is locked by other process.</td> <td>VMLocked</td> <td>403 Forbidden</td> </tr> <tr> <td>9. The cloud server was suspended.</td> <td>VMSuspended</td> <td>403 Forbidden</td> </tr> <tr> <td>10. Unsupported REST action</td> <td>NoRestMethod</td> <td>405 Not allowed method</td> </tr> <tr> <td>11. Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>12. Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	1. Expired signature	ExpiredSig	400 Bad Request	2. Invalid headers	InvalidHeader	400 Bad Request	3. Incorrect Locale code passing	InvalidLocale	400 Bad Request	4. No such member	NotExistMem	400 Bad Request	5. No such Cloud Server	NoSuchVM	400 Bad Request	6. Fail Authentication	FailAuth	403 Forbidden	7. Account problem or suspended	ACPrb	403 Forbidden	8. The cloud server is locked by other process.	VMLocked	403 Forbidden	9. The cloud server was suspended.	VMSuspended	403 Forbidden	10. Unsupported REST action	NoRestMethod	405 Not allowed method	11. Server unexpected error	UnexpectedError	500 Server error	12. Service unavailable	UnavailableService	503 Service Unavailable
Error Description	Error Code	Http Status Code																																								
1. Expired signature	ExpiredSig	400 Bad Request																																								
2. Invalid headers	InvalidHeader	400 Bad Request																																								
3. Incorrect Locale code passing	InvalidLocale	400 Bad Request																																								
4. No such member	NotExistMem	400 Bad Request																																								
5. No such Cloud Server	NoSuchVM	400 Bad Request																																								
6. Fail Authentication	FailAuth	403 Forbidden																																								
7. Account problem or suspended	ACPrb	403 Forbidden																																								
8. The cloud server is locked by other process.	VMLocked	403 Forbidden																																								
9. The cloud server was suspended.	VMSuspended	403 Forbidden																																								
10. Unsupported REST action	NoRestMethod	405 Not allowed method																																								
11. Server unexpected error	UnexpectedError	500 Server error																																								
12. Service unavailable	UnavailableService	503 Service Unavailable																																								
<b>REST Request Header</b>	POST / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjklfsj-dsfd= <i>(access_id : signature)</i>																																									



<b>REST Respond Header if success</b>	HTTP/1.1 200 OK Date: Mon, 03 Mar 2008 12:00:00 GMT Content-Length: 112 Connection: close Content-Type: application/xml
<b>REST XML Expected Result</b>	<?xml version="1.0" encoding="UTF-8" ?> <CloudServerAPI> <Status>SUCCESS</Status> </CloudServerAPI>

## API 8 – Server Subscription

Web Service Name	server_subscribe (ID_8)	REST http method	PUT																																													
<b>Description</b>	Subscribe new cloud server																																															
<b>REST example</b>	With Zone <a href="http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F/plan_code/nQ%40%28/zone_code/Spc3xH%60mKOqukM0yyDGe">http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F/plan_code/nQ%40%28/zone_code/Spc3xH%60mKOqukM0yyDGe</a>  Without Zone <a href="http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F/plan_code/nQ%40%28">http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F/plan_code/nQ%40%28</a>  Administration Mode (for super user only. General user can't use) <a href="http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F/vm_uuid/dsfjdsfjkdksfjkdksfjkdj">http://a.cserver.mygrid.asia/server_subscribe/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F/vm_uuid/dsfjdsfjkdksfjkdksfjkdj</a>																																															
<b>Http Code if success</b>	200																																															
<b>Request Signature</b>	Yes																																															
<b>Anonymous access</b>	Not accept																																															
<b>Possible Error</b>	<b>General errors</b> <table border="1" data-bbox="424 1189 1340 1680"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>400 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>400 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>400 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>403 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>403 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <b>Conditional Errors</b> <table border="1" data-bbox="424 1780 1340 2018"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Invalid IDC code</td> <td>InvalidIDCCode</td> <td>400 bad request</td> </tr> <tr> <td>Invalid Template Code</td> <td>InvalidTemplateCode</td> <td>400 bad request</td> </tr> <tr> <td>Invalid Plan Code</td> <td>InvalidPlanCode</td> <td>400 bad request</td> </tr> <tr> <td>Invalid Zone Code</td> <td>InvalidZoneCode</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	400 bad Request	Invalid headers	InvalidHeader	400 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	400 bad Request	Fail Authentication	FailAuth	403 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	403 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Invalid IDC code	InvalidIDCCode	400 bad request	Invalid Template Code	InvalidTemplateCode	400 bad request	Invalid Plan Code	InvalidPlanCode	400 bad request	Invalid Zone Code	InvalidZoneCode	400 bad request
Error Description	Error Code	Http Status Code																																														
Expired signature	ExpiredSig	400 bad Request																																														
Invalid headers	InvalidHeader	400 bad Request																																														
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																														
No such member	NotExistMem	400 bad Request																																														
Fail Authentication	FailAuth	403 Forbidden																																														
Account problem or suspended	ACPrb	403 Forbidden																																														
Unsupported REST action	NoRestMethod	403 not allowed method																																														
Server unexpected error	UnexpectedError	500 Server error																																														
Service unavailable	UnavailableService	503 Service Unavailable																																														
Error Description	Error Code	Http Status Code																																														
Invalid IDC code	InvalidIDCCode	400 bad request																																														
Invalid Template Code	InvalidTemplateCode	400 bad request																																														
Invalid Plan Code	InvalidPlanCode	400 bad request																																														
Invalid Zone Code	InvalidZoneCode	400 bad request																																														

	<table border="1"> <tr> <td>Insufficient balance to subscribe</td> <td>InsufficientBalance</td> <td>400 bad request</td> </tr> <tr> <td>Over the maximum subscription server number.</td> <td>OverMaxSubscribedServers</td> <td>400 bad request</td> </tr> <tr> <td>No stock for such template</td> <td>NoStock</td> <td>400 bad request</td> </tr> <tr> <td>No stock for template in specified zone</td> <td>NoStockInZone</td> <td>400 bad request</td> </tr> <tr> <td>No administration right</td> <td>NoAdminAccessRight</td> <td>400 bad request</td> </tr> <tr> <td>Invalid server ID you provided</td> <td>InvalidServerID</td> <td>400 bad request</td> </tr> <tr> <td>No IDC approval</td> <td>NoApproval</td> <td>400 bad request</td> </tr> <tr> <td>The demo a/c has no quota to add</td> <td>DemoACNotAllowed</td> <td>403 Forbidden</td> </tr> <tr> <td>Must provide the "Server Description"</td> <td>NotProvideServerDescription</td> <td>412 Precondition Failed</td> </tr> </table>	Insufficient balance to subscribe	InsufficientBalance	400 bad request	Over the maximum subscription server number.	OverMaxSubscribedServers	400 bad request	No stock for such template	NoStock	400 bad request	No stock for template in specified zone	NoStockInZone	400 bad request	No administration right	NoAdminAccessRight	400 bad request	Invalid server ID you provided	InvalidServerID	400 bad request	No IDC approval	NoApproval	400 bad request	The demo a/c has no quota to add	DemoACNotAllowed	403 Forbidden	Must provide the "Server Description"	NotProvideServerDescription	412 Precondition Failed
Insufficient balance to subscribe	InsufficientBalance	400 bad request																										
Over the maximum subscription server number.	OverMaxSubscribedServers	400 bad request																										
No stock for such template	NoStock	400 bad request																										
No stock for template in specified zone	NoStockInZone	400 bad request																										
No administration right	NoAdminAccessRight	400 bad request																										
Invalid server ID you provided	InvalidServerID	400 bad request																										
No IDC approval	NoApproval	400 bad request																										
The demo a/c has no quota to add	DemoACNotAllowed	403 Forbidden																										
Must provide the "Server Description"	NotProvideServerDescription	412 Precondition Failed																										
<b>More details</b>	<p>"Zone" is optional parameter. If not passing, system will random assign a zone. "idc_code", "plan_code", and "template_code" can be get from other "Query" API. i.e. API 11 – 14.</p>																											
<b>REST Request Header</b>	<p>PUT / HTTP/1.1  Host: a.cserver.mygrid.asia  Content-Length: 0  Date: Mon, 03 Mar 2008 12:00:00 +0800  <i>(or passing x-pan-date instead of Date)</i>  Authorization: 112122334214:dsfdksfjdklsfjkldsfj-dsfd= <i>(access_id : signature)</i></p>																											
<b>Possible result</b>	<p>Even the status code is "200". There are many possible situations will be returned to requester via XML.</p> <table border="1"> <thead> <tr> <th>Condition</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>condition_1</td> <td>Subscribe the server successfully. The subscribed server configuration information will be returned.</td> </tr> <tr> <td>condition_2</td> <td>The server is no stock but accept the order. It will return the template details in XML.</td> </tr> <tr> <td>condition_3</td> <td>Return error XML e.g. no stock, insufficient balance and so on.</td> </tr> </tbody> </table>	Condition	Description	condition_1	Subscribe the server successfully. The subscribed server configuration information will be returned.	condition_2	The server is no stock but accept the order. It will return the template details in XML.	condition_3	Return error XML e.g. no stock, insufficient balance and so on.																			
Condition	Description																											
condition_1	Subscribe the server successfully. The subscribed server configuration information will be returned.																											
condition_2	The server is no stock but accept the order. It will return the template details in XML.																											
condition_3	Return error XML e.g. no stock, insufficient balance and so on.																											
<b>Returned XML for condition 1</b>	<pre>&lt;NewSubscribedServer&gt; &lt;Profile&gt;   &lt;AccessID&gt;MCga6Ug851eQ1ke58sbyaCO&lt;/AccessID&gt;   &lt;LoginName&gt;peterjason&lt;/LoginName&gt;   &lt;EMail&gt;peter@jmail.com&lt;/EMail&gt; &lt;/Profile&gt; &lt;Server&gt;   &lt;ServerID&gt;938d410a-8d6-8880-cbae48b2ebef&lt;/ServerID&gt;</pre>																											

	<pre> &lt;ServerDescription&gt;first server&lt;/ServerDescription&gt; &lt;ServerPassword&gt;abcd&lt;/ServerPassword&gt; &lt;Group /&gt; &lt;Zone&gt;Zone A&lt;/Zone&gt; &lt;DNS&gt;vm1.abc.com&lt;/DNS&gt; &lt;PublicIP&gt;202.85.1.1&lt;/PublicIP&gt; &lt;IsSuspended&gt;N&lt;/IsSuspended&gt; &lt;ServerStatusCode&gt;PO&lt;/ServerStatusCode&gt; &lt;ServerStatusDescription&gt;Power Off&lt;/ServerStatusDescription&gt; &lt;ActivationDate&gt;2010-06-24 GMT&lt;/ActivationDate&gt; &lt;City&gt;Taiwan&lt;/City&gt; &lt;IDC&gt;ACT, Taiwan&lt;/IDC&gt; &lt;OSType&gt;Linux&lt;/OSType&gt; &lt;OSName&gt;Centos 5.2 (64bit)&lt;/OSName&gt; &lt;Template&gt;Centos 5.2 (64bit)&lt;/Template&gt; &lt;Plan&gt;Plan A&lt;/Plan&gt; &lt;/Server&gt; &lt;/NewSubscribedServer&gt; </pre>
<p><b>Returned XML for condition 2</b></p>	<pre> &lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;OrderedServer&gt;   &lt;IDCCode&gt;nQ%40%3B&lt;/IDCCode&gt;   &lt;IDCName&gt;ACT, Taiwan&lt;/IDCName&gt;   &lt;TemplateCode&gt;nQ%40%28F.%5Dq%26q&lt;/TemplateCode&gt;   &lt;TemplateName&gt;Centos 5.2 (64bit)&lt;/TemplateName&gt;   &lt;PlanCode&gt;nQ%40%28F.%5Dq%26q&lt;/PlanCode&gt;   &lt;PlanName&gt;Plan A&lt;/PlanName&gt;   &lt;ZoneCode&gt;Spc3xH%60mKOqukMOP&lt;/ZoneCode&gt;   &lt;ZoneName&gt;Zone A&lt;/ZoneName&gt;   &lt;WaitingDays&gt;10&lt;/WaitingDays&gt;   &lt;ServerDescription&gt;First linux server&lt;/ServerDescription&gt; &lt;/OrderedServer&gt; </pre>
<p><b>Returned XML for condition 3</b></p>	<pre> &lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;Error&gt;   &lt;ErrorCode&gt;NoStockInZone&lt;/ErrorCode&gt;   &lt;ErrorMessage&gt;No stock in this zone.&lt;/ErrorMessage&gt;   &lt;HttpStatusCode&gt;400&lt;/HttpStatusCode&gt; </pre>

	</Error>
--	----------

## API 9 – Server Termination

<b>Web Service Name</b>	<b>server_terminate (ID_9)</b>	<b>REST http method</b>	<b>DELETE</b>																																													
<b>Description</b>	Terminate a subscribed server																																															
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/server_terminate/serverid/938d410a-8de2-42a6-8880-cba/locale/en">http://a.cserver.mygrid.asia/server_terminate/serverid/938d410a-8de2-42a6-8880-cba/locale/en</a>																																															
<b>Http Code if success</b>	200																																															
<b>Request Signature</b>	Yes																																															
<b>Anonymous access</b>	Not accept																																															
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>401 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>401 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>401 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>404 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>404 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>No such cloud server</td> <td>NoSuchVM</td> <td>400 bad request</td> </tr> <tr> <td>The server is locked by other process.</td> <td>VMLocked</td> <td>403 Forbidden</td> </tr> <tr> <td>The server was suspended.</td> <td>VMSuspended</td> <td>403 Forbidden</td> </tr> <tr> <td>Fail to terminate in server side.</td> <td>FailTerminateVM</td> <td>500 internal error</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	401 bad Request	Invalid headers	InvalidHeader	401 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	401 bad Request	Fail Authentication	FailAuth	404 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	404 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	No such cloud server	NoSuchVM	400 bad request	The server is locked by other process.	VMLocked	403 Forbidden	The server was suspended.	VMSuspended	403 Forbidden	Fail to terminate in server side.	FailTerminateVM	500 internal error
Error Description	Error Code	Http Status Code																																														
Expired signature	ExpiredSig	401 bad Request																																														
Invalid headers	InvalidHeader	401 bad Request																																														
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																														
No such member	NotExistMem	401 bad Request																																														
Fail Authentication	FailAuth	404 Forbidden																																														
Account problem or suspended	ACPrb	403 Forbidden																																														
Unsupported REST action	NoRestMethod	404 not allowed method																																														
Server unexpected error	UnexpectedError	500 Server error																																														
Service unavailable	UnavailableService	503 Service Unavailable																																														
Error Description	Error Code	Http Status Code																																														
No such cloud server	NoSuchVM	400 bad request																																														
The server is locked by other process.	VMLocked	403 Forbidden																																														
The server was suspended.	VMSuspended	403 Forbidden																																														
Fail to terminate in server side.	FailTerminateVM	500 internal error																																														

<p><b>REST Request Header</b></p>	<p>DELETE / HTTP/1.1          Host: a.cserver.mygrid.asia          Content-Length: 0          Date: Mon, 03 Mar 2008 12:00:00 +0800  <i>(or passing x-pan-date instead of Date)</i>          Authorization: 112122334214:dsfdksfjdklsfjklfsfj-dsfd= <i>(access_id : signature)</i></p>
<p><b>Returned XML for success termination</b></p>	<pre>&lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;CloudServerAPI&gt; &lt;Status&gt;SUCCESS&lt;/Status&gt; &lt;/CloudServerAPI&gt;</pre>

## API 10 – Daily Billing Report

<b>Web Service Name</b>	<b>daily_billing_report (ID_10)</b>	<b>REST http method</b>	<b>GET</b>																																													
<b>Description</b>	Get daily billing records in specified date range.																																															
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/daily_billing_report/locale/en/start_date/2010-06-01/end_date/2010-06-30/offset/1/max/10">http://a.cserver.mygrid.asia/daily_billing_report/locale/en/start_date/2010-06-01/end_date/2010-06-30/offset/1/max/10</a>																																															
<b>Http Code if success</b>	200																																															
<b>Request Signature</b>	Yes																																															
<b>Anonymous access</b>	Not accept																																															
<b>More details</b>	<p>“start_date” is the starting date for report. The format should be in YYYY-MM-DD. e.g. 2010-1-1 or 2010-02-29</p> <p>“end_date” is the ending date for report. The format should be in YYYY-MM-DD. e.g. 2010-1-1 or 2010-02-29</p> <p>“offset” is used to set the starting record number . Must be 1 or greater.</p> <p>“max” is used to set the maximum return record no. Must be 1 to 30. e.g. if get record from 11<sup>th</sup> to 20<sup>th</sup>. Offset = 11 and max = 10</p>																																															
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>402 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>402 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>402 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>405 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>405 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Incorrect starting date</td> <td>InvalidBillingStartDate</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect ending date</td> <td>InvalidBillingEndDate</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect starting offset</td> <td>InvalidStartingOffset</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect maximum record number</td> <td>InvalidMaxRecordReturn</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	402 bad Request	Invalid headers	InvalidHeader	402 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	402 bad Request	Fail Authentication	FailAuth	405 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	405 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Incorrect starting date	InvalidBillingStartDate	400 bad request	Incorrect ending date	InvalidBillingEndDate	400 bad request	Incorrect starting offset	InvalidStartingOffset	400 bad request	Incorrect maximum record number	InvalidMaxRecordReturn	400 bad request
Error Description	Error Code	Http Status Code																																														
Expired signature	ExpiredSig	402 bad Request																																														
Invalid headers	InvalidHeader	402 bad Request																																														
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																														
No such member	NotExistMem	402 bad Request																																														
Fail Authentication	FailAuth	405 Forbidden																																														
Account problem or suspended	ACPrb	403 Forbidden																																														
Unsupported REST action	NoRestMethod	405 not allowed method																																														
Server unexpected error	UnexpectedError	500 Server error																																														
Service unavailable	UnavailableService	503 Service Unavailable																																														
Error Description	Error Code	Http Status Code																																														
Incorrect starting date	InvalidBillingStartDate	400 bad request																																														
Incorrect ending date	InvalidBillingEndDate	400 bad request																																														
Incorrect starting offset	InvalidStartingOffset	400 bad request																																														
Incorrect maximum record number	InvalidMaxRecordReturn	400 bad request																																														

<p><b>More details</b></p>	<p>There are many “Code” applied in returned XML.</p> <p>Account Status (A – Active, S – Suspended, T – Trial)</p> <p>PaymentModeCode (D – Daily, M – Monthly (Reserved) )</p> <p>ItemTypeCode (S – Cloud Server, C – CPU, R – RAM, LPS – SASP-6, NPS – SASP – M, IA – IP address, MD – Migratable Domain, FW – Firewall)</p> <p><b><i>P.S. Not all IDC provide same parts.</i></b></p>
<p><b>REST Request Header</b></p>	<p>GET / HTTP/1.1</p> <p>Host: a.cserver.mygrid.asia</p> <p>Content-Length: 0</p> <p>Date: Mon, 03 Mar 2008 12:00:00 +0800</p> <p><i>(or passing x-pan-date instead of Date)</i></p> <p>Authorization: 112122334214:dsfdksfjdklsfjkljsfj-dsfd= <i>(access_id : signature)</i></p>
<p><b>Returned XML</b></p>	<pre>&lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;BillingInformation&gt; &lt;Profile&gt;   &lt;AccessID&gt;ayE51eQ1ke58sbyaCO&lt;/AccessID&gt;   &lt;LoginName&gt;peterjason&lt;/LoginName&gt;   &lt;AccountStatus&gt;A&lt;/AccountStatus&gt;   &lt;CurrencyCode&gt;USD&lt;/CurrencyCode&gt;   &lt;CurrencyName&gt;US Dollars&lt;/CurrencyName&gt;   &lt;CurrencySign&gt;\$&lt;/CurrencySign&gt;   &lt;AccountBalance&gt;9,751.04&lt;/AccountBalance&gt;   &lt;OutstandingBalance&gt;0.00&lt;/OutstandingBalance&gt;   &lt;PaymentModeCode&gt;D&lt;/PaymentModeCode&gt; &lt;/Profile&gt; &lt;ResultSet&gt;   &lt;TotalNoOfRecord&gt;171&lt;/TotalNoOfRecord&gt;   &lt;StartRecordOffset&gt;1&lt;/StartRecordOffset&gt;   &lt;NoOfRecordReturn&gt;1&lt;/NoOfRecordReturn&gt;   &lt;HasMoreRecord&gt;YES&lt;/HasMoreRecord&gt; &lt;/ResultSet&gt; &lt;Transaction&gt; &lt;TransactionRecord&gt;</pre>

```
<TransactionDate>2010-06-01T23:59:59Z</TransactionDate>
<ItemTypeCode>LPS</ItemTypeCode>
<ItemDescription>50GB SASP-6 Storage</ItemDescription>
<IsValueAddedService>YES</IsValueAddedService>
<PlanID />
<PartsCode>nQ%40%28F.%5Dq%265</PartsCode>
<ResourcesUUID>APU%3FOj%282XF58jxrac</ResourcesUUID>
<Amount>0.01</Amount>
</TransactionRecord>
</Transaction>
<GrandTotal>
<TotalAmount>0.01</TotalAmount>
</GrandTotal>
</BillingInformation>
```

## API 11 – Query supported cities

<b>Web Service Name</b>	<b>query_support_city (ID_11)</b>	<b>REST http method</b>	<b>GET</b>																														
<b>Description</b>	Show which city supports cloud server																																
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/query_support_city/locale/en">http://a.cserver.mygrid.asia/query_support_city/locale/en</a>																																
<b>Http Code if success</b>	200																																
<b>Request Signature</b>	Yes																																
<b>Anonymous access</b>	Not accept																																
<b>Possible Error</b>	<b>General errors</b> <table border="1" data-bbox="422 757 1340 1249"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>403 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>403 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>403 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>406 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>406 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	403 bad Request	Invalid headers	InvalidHeader	403 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	403 bad Request	Fail Authentication	FailAuth	406 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	406 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable
Error Description	Error Code	Http Status Code																															
Expired signature	ExpiredSig	403 bad Request																															
Invalid headers	InvalidHeader	403 bad Request																															
Incorrect Locale code passing	InvalidLocale	400 Bad Request																															
No such member	NotExistMem	403 bad Request																															
Fail Authentication	FailAuth	406 Forbidden																															
Account problem or suspended	ACPrb	403 Forbidden																															
Unsupported REST action	NoRestMethod	406 not allowed method																															
Server unexpected error	UnexpectedError	500 Server error																															
Service unavailable	UnavailableService	503 Service Unavailable																															
<b>REST Request Header</b>	GET / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjkljsfj-dsfd= <i>(access_id : signature)</i>																																
<b>Returned XML</b>	<pre>&lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;QuerySupportedCity&gt; &lt;Profile&gt;   &lt;AccessID&gt;ayE51eQ1ke58sbyaCO&lt;/AccessID&gt;   &lt;LoginName&gt;peterjason&lt;/LoginName&gt;   &lt;NoOfCity&gt;2&lt;/NoOfCity&gt; &lt;/Profile&gt; &lt;CityList&gt;</pre>																																



	<pre>&lt;SupporteCity&gt;   &lt;CityName&gt;Taipei, Taiwan&lt;/CityName&gt;   &lt;CityCode&gt;nQ%40%3B&lt;/CityCode&gt; &lt;/SupporteCity&gt; &lt;SupporteCity&gt;   &lt;CityName&gt;Beijing, China&lt;/CityName&gt;   &lt;CityCode&gt;nQ%40L&lt;/CityCode&gt; &lt;/SupporteCity&gt; &lt;/CityList&gt; &lt;/QuerySupportedCity&gt;</pre>
--	--

API 12 – Query supported IDC

Web Service Name	query_support_idc (ID_12)	REST http method	GET																																							
<b>Description</b>	Show which data center supports cloud server in a city. Or, Show which data center provide specified service such as SASP-M.																																									
<b>REST example</b>	There are 2 URI methods. Method 1 (show IDC under specified city) : <a href="http://a.cserver.mygrid.asia/query_support_idc/locale/en/citycode/nQ%40%3B">http://a.cserver.mygrid.asia/query_support_idc/locale/en/citycode/nQ%40%3B</a>  Method 2 (show IDC under specified service) : <a href="http://a.cserver.mygrid.asia/query_support_idc/locale/en/service_type/saspm">http://a.cserver.mygrid.asia/query_support_idc/locale/en/service_type/saspm</a>																																									
<b>Http Code if success</b>	200																																									
<b>Request Signature</b>	Yes																																									
<b>Anonymous access</b>	Not accept																																									
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>404 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>404 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>404 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>407 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>407 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Incorrect city code</td> <td>InvalidCityCode</td> <td>400 bad request</td> </tr> <tr> <td>No such service</td> <td>NoSuchService</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	404 bad Request	Invalid headers	InvalidHeader	404 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	404 bad Request	Fail Authentication	FailAuth	407 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	407 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Incorrect city code	InvalidCityCode	400 bad request	No such service	NoSuchService	400 bad request
Error Description	Error Code	Http Status Code																																								
Expired signature	ExpiredSig	404 bad Request																																								
Invalid headers	InvalidHeader	404 bad Request																																								
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																								
No such member	NotExistMem	404 bad Request																																								
Fail Authentication	FailAuth	407 Forbidden																																								
Account problem or suspended	ACPrb	403 Forbidden																																								
Unsupported REST action	NoRestMethod	407 not allowed method																																								
Server unexpected error	UnexpectedError	500 Server error																																								
Service unavailable	UnavailableService	503 Service Unavailable																																								
Error Description	Error Code	Http Status Code																																								
Incorrect city code	InvalidCityCode	400 bad request																																								
No such service	NoSuchService	400 bad request																																								



<p><b>REST Request</b></p> <p><b>Header</b></p>	<p>GET / HTTP/1.1</p> <p>Host: a.cserver.mygrid.asia</p> <p>Content-Length: 0</p> <p>Date: Mon, 03 Mar 2008 12:00:00 +0800</p> <p><i>(or passing x-pan-date instead of Date)</i></p> <p>Authorization: 112122334214:dsfdksfjdklsfjklfsfj-dsfd= <i>(access_id : signature)</i></p>
<p><b>Returned XML</b></p>	<pre> &lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;QuerySupportedIDC&gt; &lt;Profile&gt;   &lt;AccessID&gt;ayE51eQ1ke58sbyaCO&lt;/AccessID&gt;   &lt;LoginName&gt;peterjason&lt;/LoginName&gt;   &lt;NoOfIDC&gt;3&lt;/NoOfIDC&gt; &lt;/Profile&gt; &lt;IDCList&gt; &lt;SupporteIDC&gt;   &lt;IDCName&gt;PCCW, Hong Kong&lt;/IDCName&gt;   &lt;IDCCode&gt;nQ%40%3B&lt;/IDCCode&gt; &lt;/SupporteIDC&gt; &lt;SupporteIDC&gt;   &lt;IDCName&gt;TRUE, Thailand&lt;/IDCName&gt;   &lt;IDCCode&gt;nQ%40t&lt;/IDCCode&gt; &lt;/SupporteIDC&gt; &lt;SupporteIDC&gt;   &lt;IDCName&gt;ACT, Taiwan&lt;/IDCName&gt;   &lt;IDCCode&gt;nQ%40- &lt;/IDCCode&gt; &lt;/SupporteIDC&gt; &lt;/IDCList&gt; &lt;/QuerySupportedIDC&gt; </pre>

API 13 – Query supported template

<b>Web Service Name</b>	<b>query_support_template (ID_13)</b>	<b>REST http method</b>	<b>GET</b>																																				
<b>Description</b>	Show what templates are available in specified city. It includes “Standard”, “Custom” templates and “Zone”.																																						
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/query_support_template/locale/en/idc_code/nQ%3B">http://a.cserver.mygrid.asia/query_support_template/locale/en/idc_code/nQ%3B</a>																																						
<b>Http Code if success</b>	200																																						
<b>Request Signature</b>	Yes																																						
<b>Anonymous access</b>	Not accept																																						
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>405 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>405 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>405 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>408 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>408 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Incorrect IDC code</td> <td>InvalidIDCCode</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	405 bad Request	Invalid headers	InvalidHeader	405 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	405 bad Request	Fail Authentication	FailAuth	408 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	408 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Incorrect IDC code	InvalidIDCCode	400 bad request
Error Description	Error Code	Http Status Code																																					
Expired signature	ExpiredSig	405 bad Request																																					
Invalid headers	InvalidHeader	405 bad Request																																					
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																					
No such member	NotExistMem	405 bad Request																																					
Fail Authentication	FailAuth	408 Forbidden																																					
Account problem or suspended	ACPrb	403 Forbidden																																					
Unsupported REST action	NoRestMethod	408 not allowed method																																					
Server unexpected error	UnexpectedError	500 Server error																																					
Service unavailable	UnavailableService	503 Service Unavailable																																					
Error Description	Error Code	Http Status Code																																					
Incorrect IDC code	InvalidIDCCode	400 bad request																																					
<b>REST Request Header</b>	GET / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjklfsfj-dsfd= <i>(access_id : signature)</i>																																						

<p><b>Returned XML</b></p>	<pre> &lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;QuerySupportedTemplate&gt; &lt;Profile&gt;   &lt;AccessID&gt;yayE51eQ1ke58sbyaCO&lt;/AccessID&gt;   &lt;LoginName&gt;peterjason&lt;/LoginName&gt; &lt;/Profile&gt; &lt;ZoneList&gt;   &lt;NoOfZone&gt;2&lt;/NoOfZone&gt; &lt;ZoneRecord&gt;   &lt;ZoneName&gt;Zone A&lt;/ZoneName&gt;   &lt;ZoneCode&gt;Spc3xH%60mKOqkM%2Bld%5DU8cGF%7Br%7E6P&lt;/ZoneCode&gt; &lt;/ZoneRecord&gt; &lt;ZoneRecord&gt;   &lt;ZoneName&gt;Zone B&lt;/ZoneName&gt;   &lt;ZoneCode&gt;c8j3_%2CYFGKkoYl%33%7CXT%7ER6%7DVI&lt;/ZoneCode&gt; &lt;/ZoneRecord&gt; &lt;/ZoneList&gt; &lt;StandardTemplateList&gt;   &lt;NoOfStandardTemplate&gt;2&lt;/NoOfStandardTemplate&gt; &lt;StandardTemplate&gt;   &lt;TemplateName&gt;Centos 5.2 (64bit)&lt;/TemplateName&gt;   &lt;TemplateCode&gt;nQ%40%28F.%5Dq%26q&lt;/TemplateCode&gt;   &lt;HaveStockNow&gt;Y&lt;/HaveStockNow&gt;   &lt;PrepareDays&gt;0&lt;/PrepareDays&gt; &lt;/StandardTemplate&gt; &lt;StandardTemplate&gt;   &lt;TemplateName&gt;Centos 5.2 (32bit) (Out of Stock, need 2 days of   delivery.)&lt;/TemplateName&gt;   &lt;TemplateCode&gt;nQ%40%28F.%5Dq%261&lt;/TemplateCode&gt;   &lt;HaveStockNow&gt;N&lt;/HaveStockNow&gt;   &lt;PrepareDays&gt;2&lt;/PrepareDays&gt; &lt;/StandardTemplate&gt; &lt;/StandardTemplateList&gt; &lt;IDCTemplateList&gt;   &lt;NoOfIDCTemplate&gt;1&lt;/NoOfIDCTemplate&gt; &lt;IDCTemplate&gt; </pre>
----------------------------	--



## Cloud Server API – Development Guideline

	<pre>&lt;TemplateName&gt;IDC Template&lt;/TemplateName&gt; &lt;TemplateCode&gt;nQ%40%28F.%5Dq57&lt;/TemplateCode&gt; &lt;HaveStockNow&gt;Y&lt;/HaveStockNow&gt; &lt;PrepareDays&gt;0&lt;/PrepareDays&gt; &lt;/IDCTemplate&gt; &lt;/IDCTemplateList&gt; &lt;/QuerySupportedTemplate&gt;</pre>
--	--

## API 14 – Query template’s plan

<b>Web Service Name</b>	<b>query_template_plan (ID_14)</b>	<b>REST http method</b>	<b>GET</b>																																							
<b>Description</b>	Show all plans for specified template.																																									
<b>REST example</b>	<a href="http://a.cserver.mygrid.asia/query_template_price/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F.%5Dq%26q">http://a.cserver.mygrid.asia/query_template_price/locale/en/idc_code/nQ%40%3B/template_code/nQ%40%28F.%5Dq%26q</a>																																									
<b>Http Code if success</b>	200																																									
<b>Request Signature</b>	Yes																																									
<b>Anonymous access</b>	Not accept																																									
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>406 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>406 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>406 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>409 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>409 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Incorrect IDC code</td> <td>InvalidIDCCode</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect template code</td> <td>InvalidTemplateCode</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	406 bad Request	Invalid headers	InvalidHeader	406 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	406 bad Request	Fail Authentication	FailAuth	409 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	409 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Incorrect IDC code	InvalidIDCCode	400 bad request	Incorrect template code	InvalidTemplateCode	400 bad request
Error Description	Error Code	Http Status Code																																								
Expired signature	ExpiredSig	406 bad Request																																								
Invalid headers	InvalidHeader	406 bad Request																																								
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																								
No such member	NotExistMem	406 bad Request																																								
Fail Authentication	FailAuth	409 Forbidden																																								
Account problem or suspended	ACPrb	403 Forbidden																																								
Unsupported REST action	NoRestMethod	409 not allowed method																																								
Server unexpected error	UnexpectedError	500 Server error																																								
Service unavailable	UnavailableService	503 Service Unavailable																																								
Error Description	Error Code	Http Status Code																																								
Incorrect IDC code	InvalidIDCCode	400 bad request																																								
Incorrect template code	InvalidTemplateCode	400 bad request																																								
<b>REST Request Header</b>	GET / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjklfsfj-dsfd= <i>(access_id : signature)</i>																																									

<p><b>Returned XML</b></p>	<pre> &lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;QueryTemplatePrice&gt;   &lt;Profile&gt;     &lt;AccessID&gt;RWyayE51eQ1ke58sbyaCO&lt;/AccessID&gt;     &lt;LoginName&gt;peterjason&lt;/LoginName&gt;     &lt;Currency&gt;USD&lt;/Currency&gt;   &lt;/Profile&gt;   &lt;PlanList&gt;     &lt;NoOfPlan&gt;2&lt;/NoOfPlan&gt;     &lt;PlanDetail&gt;       &lt;PlanName&gt;Plan A&lt;/PlanName&gt;       &lt;PlanCode&gt;nQ%40%28F.%5Dq%26q&lt;/PlanCode&gt;       &lt;VirtualCPU&gt;1&lt;/VirtualCPU&gt;       &lt;RAMSize&gt;256&lt;/RAMSize&gt;       &lt;RAMSizeUnit&gt;MB&lt;/RAMSizeUnit&gt;       &lt;HardDiskSize&gt;10&lt;/HardDiskSize&gt;       &lt;HardDiskSizeUnit&gt;GB&lt;/HardDiskSizeUnit&gt;       &lt;Price&gt;0.01&lt;/Price&gt;     &lt;/PlanDetail&gt;     &lt;PlanDetail&gt;       &lt;PlanName&gt;Plan B&lt;/PlanName&gt;       &lt;PlanCode&gt;nQ%40%28F.%5Dq%261&lt;/PlanCode&gt;       &lt;VirtualCPU&gt;20&lt;/VirtualCPU&gt;       &lt;RAMSize&gt;512&lt;/RAMSize&gt;       &lt;RAMSizeUnit&gt;MB&lt;/RAMSizeUnit&gt;       &lt;HardDiskSize&gt;11&lt;/HardDiskSize&gt;       &lt;HardDiskSizeUnit&gt;GB&lt;/HardDiskSizeUnit&gt;       &lt;Price&gt;0.01&lt;/Price&gt;     &lt;/PlanDetail&gt;   &lt;/PlanList&gt; &lt;/QueryTemplatePrice&gt; </pre>
----------------------------	---

## API 15 – Query extra parts' plan

<b>Web Service Name</b>	<b>query_extra_parts_plan (ID_15)</b>	<b>REST http method</b>	<b>GET</b>																																										
<b>Description</b>	Show extra parts' price plan. e.g. CPU/RAM/SASP-6/SASP-M																																												
<b>REST example</b>	There are 2 URI formats supported. Method 1 : query for CPU/RAM/SASP-6 <a href="http://a.cserver.mygrid.asia/query_extra_parts_plan/locale/en/serverid/111111/service_type/cpu">http://a.cserver.mygrid.asia/query_extra_parts_plan/locale/en/serverid/111111/service_type/cpu</a> or Method 2 : query for SASP-M <a href="http://a.cserver.mygrid.asia/query_extra_parts_plan/locale/en/idc_code/111/service_type/saspm">http://a.cserver.mygrid.asia/query_extra_parts_plan/locale/en/idc_code/111/service_type/saspm</a>																																												
<b>Http Code if success</b>	200																																												
<b>Request Signature</b>	Yes																																												
<b>Anonymous access</b>	Not accept																																												
<b>Possible Error</b>	<b>General errors</b> <table border="1" data-bbox="424 1093 1340 1585"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>407 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>407 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>407 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>410 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>410 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <b>Conditional Errors</b> <table border="1" data-bbox="424 1731 1340 1926"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Incorrect IDC code</td> <td>InvalidIDCCode</td> <td>400 bad request</td> </tr> <tr> <td>No such service</td> <td>NoSuchService</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect server ID</td> <td>InvalidServerID</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	407 bad Request	Invalid headers	InvalidHeader	407 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	407 bad Request	Fail Authentication	FailAuth	410 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	410 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Incorrect IDC code	InvalidIDCCode	400 bad request	No such service	NoSuchService	400 bad request	Incorrect server ID	InvalidServerID	400 bad request
Error Description	Error Code	Http Status Code																																											
Expired signature	ExpiredSig	407 bad Request																																											
Invalid headers	InvalidHeader	407 bad Request																																											
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																											
No such member	NotExistMem	407 bad Request																																											
Fail Authentication	FailAuth	410 Forbidden																																											
Account problem or suspended	ACPrb	403 Forbidden																																											
Unsupported REST action	NoRestMethod	410 not allowed method																																											
Server unexpected error	UnexpectedError	500 Server error																																											
Service unavailable	UnavailableService	503 Service Unavailable																																											
Error Description	Error Code	Http Status Code																																											
Incorrect IDC code	InvalidIDCCode	400 bad request																																											
No such service	NoSuchService	400 bad request																																											
Incorrect server ID	InvalidServerID	400 bad request																																											

<p><b>REST Request Header</b></p>	<p>GET / HTTP/1.1</p> <p>Host: a.cserver.mygrid.asia</p> <p>Content-Length: 0</p> <p>Date: Mon, 03 Mar 2008 12:00:00 +0800</p> <p><i>(or passing x-pan-date instead of Date)</i></p> <p>Authorization: 112122334214:dsfdksfjdklsfjkljsfd= <i>(access_id : signature)</i></p>
<p><b>Returned XML</b></p>	<p>Following is example XML output for SASP-6. If you query for other parts, the output has slightly different on content.</p> <pre> &lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;QueryExtraPartsPlan&gt; &lt;Profile&gt;   &lt;AccessID&gt;Ma6Ug8ORWyayE51eQ1ke58sbyaCO&lt;/AccessID&gt;   &lt;LoginName&gt;david&lt;/LoginName&gt;   &lt;PartsType&gt;sasp6&lt;/PartsType&gt;   &lt;NoOfPlan&gt;4&lt;/NoOfPlan&gt; &lt;/Profile&gt; &lt;PlanList&gt; &lt;SupportedPlan&gt;   &lt;PartsCode&gt;nQ%40%28F.%5Dq%265&lt;/PartsCode&gt;   &lt;PlanDesc&gt;Plan A&lt;/PlanDesc&gt;   &lt;Disk_Size_In_GB&gt;1&lt;/Disk_Size_In_GB&gt;   &lt;Currency&gt;USD&lt;/Currency&gt;   &lt;DollarSign&gt;\$&lt;/DollarSign&gt;   &lt;Amount&gt;0.03&lt;/Amount&gt; &lt;/SupportedPlan&gt; &lt;SupportedPlan&gt;   &lt;PartsCode&gt;nQ%40%28F.%5Dq%26w&lt;/PartsCode&gt;   &lt;PlanDesc&gt;Plan B&lt;/PlanDesc&gt;   &lt;Disk_Size_In_GB&gt;2&lt;/Disk_Size_In_GB&gt;   &lt;Currency&gt;USD&lt;/Currency&gt;   &lt;DollarSign&gt;\$&lt;/DollarSign&gt;   &lt;Amount&gt;0.01&lt;/Amount&gt; &lt;/SupportedPlan&gt; &lt;SupportedPlan&gt; </pre>

```
<PartsCode>nQ%40%28F.%5Dq%26_</PartsCode>
<PlanDesc>Plan C</PlanDesc>
<Disk_Size_In_GB>3</Disk_Size_In_GB>
<Currency>USD</Currency>
<DollarSign>$</DollarSign>
<Amount>0.01</Amount>
</SupportedPlan>
<SupportedPlan>
<PartsCode>nQ%40%28F.%5Dqq</PartsCode>
<PlanDesc>Plan D</PlanDesc>
<Disk_Size_In_GB>4</Disk_Size_In_GB>
<Currency>USD</Currency>
<DollarSign>$</DollarSign>
<Amount>0.01</Amount>
</SupportedPlan>
</PlanList>
</QueryExtraPartsPlan>
```

API 16 – Add extra parts

Web Service Name	add_extra_parts (ID_16)	REST http method	PUT																																																
<b>Description</b>	Add extra parts to specified server or IDC.																																																		
<b>REST example</b>	<p>There are 2 URI formats supported.</p> <p>Method 1 : Add CPU/RAM/SASP-6</p> <p><a href="http://a.cserver.mygrid.asia/add_extra_parts/locale/en/serverid/11111/service_type/ram/parts_code/xyz">http://a.cserver.mygrid.asia/add_extra_parts/locale/en/serverid/11111/service_type/ram/parts_code/xyz</a></p> <p>or</p> <p>Method 2 : Add SASP-M</p> <p><a href="http://a.cserver.mygrid.asia/add_extra_parts/locale/en/idc_code/00001/service_type/saspm/parts_code/xyz">http://a.cserver.mygrid.asia/add_extra_parts/locale/en/idc_code/00001/service_type/saspm/parts_code/xyz</a></p>																																																		
<b>Http Code if success</b>	200																																																		
<b>Request Signature</b>	Yes																																																		
<b>Anonymous access</b>	Not accept																																																		
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>408 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>408 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>408 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>411 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>411 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Invalid IDC code</td> <td>InvalidIDCCode</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect server ID</td> <td>InvalidServerID</td> <td>400 bad request</td> </tr> <tr> <td>No such service</td> <td>NoSuchService</td> <td>400 bad request</td> </tr> <tr> <td>Invalid parts</td> <td>InvalidParts</td> <td>400 bad request</td> </tr> <tr> <td>Insufficient balance to subscribe</td> <td>InsufficientBalance</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	408 bad Request	Invalid headers	InvalidHeader	408 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	408 bad Request	Fail Authentication	FailAuth	411 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	411 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Invalid IDC code	InvalidIDCCode	400 bad request	Incorrect server ID	InvalidServerID	400 bad request	No such service	NoSuchService	400 bad request	Invalid parts	InvalidParts	400 bad request	Insufficient balance to subscribe	InsufficientBalance	400 bad request
Error Description	Error Code	Http Status Code																																																	
Expired signature	ExpiredSig	408 bad Request																																																	
Invalid headers	InvalidHeader	408 bad Request																																																	
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																																	
No such member	NotExistMem	408 bad Request																																																	
Fail Authentication	FailAuth	411 Forbidden																																																	
Account problem or suspended	ACPrb	403 Forbidden																																																	
Unsupported REST action	NoRestMethod	411 not allowed method																																																	
Server unexpected error	UnexpectedError	500 Server error																																																	
Service unavailable	UnavailableService	503 Service Unavailable																																																	
Error Description	Error Code	Http Status Code																																																	
Invalid IDC code	InvalidIDCCode	400 bad request																																																	
Incorrect server ID	InvalidServerID	400 bad request																																																	
No such service	NoSuchService	400 bad request																																																	
Invalid parts	InvalidParts	400 bad request																																																	
Insufficient balance to subscribe	InsufficientBalance	400 bad request																																																	

	No such server	NoSuchVM	400 bad request
	Server should be shutdown	MustShutdownServer	400 bad request
	Over max allowed CPU no.	ExceedMaxCPU	400 bad request
	Over max allowed RAM size	ExceedMaxRAM	400 bad request
	Over max allowed connect drive no.	ExceedMaxDriveNo	400 bad request
	Fail to adjust CPU	FailAdjustCPUNumber	400 bad request
	Fail to adjust RAM size	FailAdjustRAMSize	400 bad request
	Fail to add hard drive	FailAddDrive	400 bad request
	Server was suspended before	VMSuspended	403 forbidden
	Server is locked by other procedure	VMLocked	403 forbidden
<b>REST Request Header</b>	PUT / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjkl dsfj-dsfd= <i>(access_id : signature)</i>		
<b>Returned XML for</b>	- <CloudServerAPI> <Status>SUCCESS</Status> </CloudServerAPI>		

## API 17 – Query subscribed parts

<b>Web Service Name</b>	<b>query_extra_subscribed_service (ID_17)</b>	<b>REST http method</b>	<b>GET</b>																																				
<b>Description</b>	Show what parts are subscribed.																																						
<b>REST example</b>	e.g. <a href="http://a.cserver.mygrid.asia/query_extra_subscribed_service/locale/en/service_type/cpu">http://a.cserver.mygrid.asia/query_extra_subscribed_service/locale/en/service_type/cpu</a>																																						
<b>Http Code if success</b>	200																																						
<b>Request Signature</b>	Yes																																						
<b>Anonymous access</b>	Not accept																																						
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>409 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>409 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>409 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>412 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>412 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>No such service</td> <td>NoSuchService</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	409 bad Request	Invalid headers	InvalidHeader	409 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	409 bad Request	Fail Authentication	FailAuth	412 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	412 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	No such service	NoSuchService	400 bad request
Error Description	Error Code	Http Status Code																																					
Expired signature	ExpiredSig	409 bad Request																																					
Invalid headers	InvalidHeader	409 bad Request																																					
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																					
No such member	NotExistMem	409 bad Request																																					
Fail Authentication	FailAuth	412 Forbidden																																					
Account problem or suspended	ACPrb	403 Forbidden																																					
Unsupported REST action	NoRestMethod	412 not allowed method																																					
Server unexpected error	UnexpectedError	500 Server error																																					
Service unavailable	UnavailableService	503 Service Unavailable																																					
Error Description	Error Code	Http Status Code																																					
No such service	NoSuchService	400 bad request																																					
<b>REST Request Header</b>	GET / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjklfsj-dsfd= <i>(access_id : signature)</i>																																						

<p><b>Returned XML</b></p>	<pre> &lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;QueryExtraSubscribedService&gt; &lt;Profile&gt;   &lt;AccessID&gt;M6Ug8ORWyayE51eQ1ke58sbyaCO&lt;/AccessID&gt;   &lt;LoginName&gt;david&lt;/LoginName&gt;   &lt;PartsType&gt;cpu&lt;/PartsType&gt;   &lt;NoOfRecord&gt;2&lt;/NoOfRecord&gt; &lt;/Profile&gt; &lt;ExtraList&gt; &lt;ExtraParts&gt;   &lt;IDC&gt;Sapura, Malaysia&lt;/IDC&gt;   &lt;ServerID&gt;e80224f0-7aa6-44b5-bc80-ba47f06bb42d&lt;/ServerID&gt;   &lt;CPU_Parts_ID&gt;f4a2c788-48ea-41a3-843b-8df0fbc6973c&lt;/CPU_Parts_ID&gt;   &lt;No_Of_CPU&gt;1&lt;/No_Of_CPU&gt; &lt;/ExtraParts&gt; &lt;ExtraParts&gt;   &lt;IDC&gt;Sapura, Malaysia&lt;/IDC&gt;   &lt;ServerID&gt;e80224f0-7aa6-44b5-bc80-ba47f06bb42d&lt;/ServerID&gt;   &lt;CPU_Parts_ID&gt;ff8d5708-3207-4805-8454-916d04b22991&lt;/CPU_Parts_ID&gt;   &lt;No_Of_CPU&gt;1&lt;/No_Of_CPU&gt; &lt;/ExtraParts&gt; &lt;/ExtraList&gt; &lt;/QueryExtraSubscribedService&gt; </pre>
----------------------------	---

## API 18– Remove subscribed parts

Web Service Name	remove_extra_parts (ID_18)	REST http method	DELETE																																																
<b>Description</b>	Remove subscribed extra parts from server or IDC.																																																		
<b>REST example</b>	There are 2 URI formats supported. Method 1 : query for CPU/RAM/SASP-6 <a href="http://a.cserver.mygrid.asia/remove_extra_parts/locale/en/serverid/111111/service_type/cpu/parts_id/abcdef">http://a.cserver.mygrid.asia/remove_extra_parts/locale/en/serverid/111111/service_type/cpu/parts_id/abcdef</a> or Method 2 : query for SASP-M <a href="http://a.cserver.mygrid.asia/remove_extra_parts/locale/en/service_type/saspm/parts_id/zyx">http://a.cserver.mygrid.asia/remove_extra_parts/locale/en/service_type/saspm/parts_id/zyx</a>																																																		
<b>Http Code if success</b>	200																																																		
<b>Request Signature</b>	Yes																																																		
<b>Anonymous access</b>	Not accept																																																		
<b>Possible Error</b>	<b>General errors</b> <table border="1" data-bbox="424 1093 1340 1585"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>410 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>410 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>410 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>413 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>413 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <b>Conditional Errors</b> <table border="1" data-bbox="424 1731 1340 2018"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Invalid parts</td> <td>InvalidParts</td> <td>400 bad request</td> </tr> <tr> <td>No such service</td> <td>NoSuchService</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect server ID</td> <td>InvalidServerID</td> <td>400 bad request</td> </tr> <tr> <td>Server should be shutdown</td> <td>MustShutdownServer</td> <td>400 bad request</td> </tr> <tr> <td>Parts was removed before</td> <td>PartsRemovedBefore</td> <td>400 bad request</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	410 bad Request	Invalid headers	InvalidHeader	410 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	410 bad Request	Fail Authentication	FailAuth	413 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	413 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Invalid parts	InvalidParts	400 bad request	No such service	NoSuchService	400 bad request	Incorrect server ID	InvalidServerID	400 bad request	Server should be shutdown	MustShutdownServer	400 bad request	Parts was removed before	PartsRemovedBefore	400 bad request
Error Description	Error Code	Http Status Code																																																	
Expired signature	ExpiredSig	410 bad Request																																																	
Invalid headers	InvalidHeader	410 bad Request																																																	
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																																	
No such member	NotExistMem	410 bad Request																																																	
Fail Authentication	FailAuth	413 Forbidden																																																	
Account problem or suspended	ACPrb	403 Forbidden																																																	
Unsupported REST action	NoRestMethod	413 not allowed method																																																	
Server unexpected error	UnexpectedError	500 Server error																																																	
Service unavailable	UnavailableService	503 Service Unavailable																																																	
Error Description	Error Code	Http Status Code																																																	
Invalid parts	InvalidParts	400 bad request																																																	
No such service	NoSuchService	400 bad request																																																	
Incorrect server ID	InvalidServerID	400 bad request																																																	
Server should be shutdown	MustShutdownServer	400 bad request																																																	
Parts was removed before	PartsRemovedBefore	400 bad request																																																	



## Cloud Server API – Development Guideline

	Parts type incorrect	InvalidPartsType	400 bad request
	Fail to adjust CPU	FailAdjustCPUNumber	400 bad request
	Fail to adjust RAM size	FailAdjustRAMSize	400 bad request
	Fail to remove hard drive	FailRemoveDrive	400 bad request
	Server was suspended before	VMSuspended	403 forbidden
	Server is locked by other procedure	VMLocked	403 forbidden
<b>REST Request Header</b>	DELETE / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjklfsfj-dsfd= <i>(access_id : signature)</i>		
<b>Returned XML</b>	<CloudServerAPI> <Status>SUCCESS</Status> </CloudServerAPI>		

## API 19 – Attach SASP-M disk

<b>Web Service Name</b>	<b>attach_disk (ID_19)</b>	<b>REST http method</b>	<b>PUT</b>																																																															
<b>Description</b>	Attach SASP-M disk to specified server.																																																																	
<b>REST example</b>	e.g. <a href="http://a.cserver.mygrid.asia/attach_disk/locale/en/serverid/11111/parts_id/abcdefg">http://a.cserver.mygrid.asia/attach_disk/locale/en/serverid/11111/parts_id/abcdefg</a>																																																																	
<b>Http Code if success</b>	200																																																																	
<b>Request Signature</b>	Yes																																																																	
<b>Anonymous access</b>	Not accept																																																																	
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>411 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>411 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>411 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>414 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>414 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Server should be shutdown</td> <td>MustShutdownServer</td> <td>400 bad request</td> </tr> <tr> <td>Invalid parts ID</td> <td>InvalidPartsID</td> <td>400 bad request</td> </tr> <tr> <td>Parts was removed before</td> <td>PartsRemovedBefore</td> <td>400 bad request</td> </tr> <tr> <td>Invalid parts type</td> <td>InvalidPartsType</td> <td>400 bad request</td> </tr> <tr> <td>Disk was attached before</td> <td>DiskAttachedBefore</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect server ID</td> <td>InvalidServerID</td> <td>400 bad request</td> </tr> <tr> <td>Over allowed max drive no.</td> <td>ExceedMaxDriveNo</td> <td>400 bad request</td> </tr> <tr> <td>Fail to attach drive</td> <td>FailAttachDrive</td> <td>400 bad request</td> </tr> <tr> <td>Server was suspended before</td> <td>VMSuspended</td> <td>403 forbidden</td> </tr> <tr> <td>Server is locked by other procedure</td> <td>VMLocked</td> <td>403 forbidden</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	411 bad Request	Invalid headers	InvalidHeader	411 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	411 bad Request	Fail Authentication	FailAuth	414 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	414 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Server should be shutdown	MustShutdownServer	400 bad request	Invalid parts ID	InvalidPartsID	400 bad request	Parts was removed before	PartsRemovedBefore	400 bad request	Invalid parts type	InvalidPartsType	400 bad request	Disk was attached before	DiskAttachedBefore	400 bad request	Incorrect server ID	InvalidServerID	400 bad request	Over allowed max drive no.	ExceedMaxDriveNo	400 bad request	Fail to attach drive	FailAttachDrive	400 bad request	Server was suspended before	VMSuspended	403 forbidden	Server is locked by other procedure	VMLocked	403 forbidden
Error Description	Error Code	Http Status Code																																																																
Expired signature	ExpiredSig	411 bad Request																																																																
Invalid headers	InvalidHeader	411 bad Request																																																																
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																																																
No such member	NotExistMem	411 bad Request																																																																
Fail Authentication	FailAuth	414 Forbidden																																																																
Account problem or suspended	ACPrb	403 Forbidden																																																																
Unsupported REST action	NoRestMethod	414 not allowed method																																																																
Server unexpected error	UnexpectedError	500 Server error																																																																
Service unavailable	UnavailableService	503 Service Unavailable																																																																
Error Description	Error Code	Http Status Code																																																																
Server should be shutdown	MustShutdownServer	400 bad request																																																																
Invalid parts ID	InvalidPartsID	400 bad request																																																																
Parts was removed before	PartsRemovedBefore	400 bad request																																																																
Invalid parts type	InvalidPartsType	400 bad request																																																																
Disk was attached before	DiskAttachedBefore	400 bad request																																																																
Incorrect server ID	InvalidServerID	400 bad request																																																																
Over allowed max drive no.	ExceedMaxDriveNo	400 bad request																																																																
Fail to attach drive	FailAttachDrive	400 bad request																																																																
Server was suspended before	VMSuspended	403 forbidden																																																																
Server is locked by other procedure	VMLocked	403 forbidden																																																																



<p><b>REST Request</b></p> <p><b>Header</b></p>	<p>PUT / HTTP/1.1</p> <p>Host: a.cserver.mygrid.asia</p> <p>Content-Length: 0</p> <p>Date: Mon, 03 Mar 2008 12:00:00 +0800</p> <p><i>(or passing x-pan-date instead of Date)</i></p> <p>Authorization: 112122334214:dsfdksfjdklsfjklfsfj-dsfd= <i>(access_id : signature)</i></p>
<p><b>Returned XML</b></p>	<pre>&lt;?xml version="1.0" encoding="UTF-8" ?&gt; &lt;&lt;CloudServerAPI&gt;   &lt;Status&gt;SUCCESS&lt;/Status&gt; &lt;/CloudServerAPI&gt;</pre>

## API 20 – Detach SASP-M disk

<b>Web Service Name</b>	<b>detach_disk (ID_20)</b>	<b>REST http method</b>	<b>DELETE</b>																																																												
<b>Description</b>	Detach SASP-M disk from specified server.																																																														
<b>REST example</b>	e.g. <a href="http://a.cserver.mygrid.asia/detach_disk/locale/en/serverid/1111/parts_id/abcdefg">http://a.cserver.mygrid.asia/detach_disk/locale/en/serverid/1111/parts_id/abcdefg</a>																																																														
<b>Http Code if success</b>	200																																																														
<b>Request Signature</b>	Yes																																																														
<b>Anonymous access</b>	Not accept																																																														
<b>Possible Error</b>	<p><b>General errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Expired signature</td> <td>ExpiredSig</td> <td>412 bad Request</td> </tr> <tr> <td>Invalid headers</td> <td>InvalidHeader</td> <td>412 bad Request</td> </tr> <tr> <td>Incorrect Locale code passing</td> <td>InvalidLocale</td> <td>400 Bad Request</td> </tr> <tr> <td>No such member</td> <td>NotExistMem</td> <td>412 bad Request</td> </tr> <tr> <td>Fail Authentication</td> <td>FailAuth</td> <td>415 Forbidden</td> </tr> <tr> <td>Account problem or suspended</td> <td>ACPrb</td> <td>403 Forbidden</td> </tr> <tr> <td>Unsupported REST action</td> <td>NoRestMethod</td> <td>415 not allowed method</td> </tr> <tr> <td>Server unexpected error</td> <td>UnexpectedError</td> <td>500 Server error</td> </tr> <tr> <td>Service unavailable</td> <td>UnavailableService</td> <td>503 Service Unavailable</td> </tr> </tbody> </table> <p><b>Conditional Errors</b></p> <table border="1"> <thead> <tr> <th>Error Description</th> <th>Error Code</th> <th>Http Status Code</th> </tr> </thead> <tbody> <tr> <td>Server should be shutdown</td> <td>MustShutdownServer</td> <td>400 bad request</td> </tr> <tr> <td>Invalid parts ID</td> <td>InvalidPartsID</td> <td>400 bad request</td> </tr> <tr> <td>Parts was removed before</td> <td>PartsRemovedBefore</td> <td>400 bad request</td> </tr> <tr> <td>Invalid parts type</td> <td>InvalidPartsType</td> <td>400 bad request</td> </tr> <tr> <td>Disk was detached before</td> <td>DiskDetachedBefore</td> <td>400 bad request</td> </tr> <tr> <td>Incorrect server ID</td> <td>InvalidServerID</td> <td>400 bad request</td> </tr> <tr> <td>Fail to detach drive</td> <td>FailDetachDrive</td> <td>400 bad request</td> </tr> <tr> <td>Server was suspended before</td> <td>VMSuspended</td> <td>403 forbidden</td> </tr> <tr> <td>Server is locked by other procedure</td> <td>VMLocked</td> <td>403 forbidden</td> </tr> </tbody> </table>			Error Description	Error Code	Http Status Code	Expired signature	ExpiredSig	412 bad Request	Invalid headers	InvalidHeader	412 bad Request	Incorrect Locale code passing	InvalidLocale	400 Bad Request	No such member	NotExistMem	412 bad Request	Fail Authentication	FailAuth	415 Forbidden	Account problem or suspended	ACPrb	403 Forbidden	Unsupported REST action	NoRestMethod	415 not allowed method	Server unexpected error	UnexpectedError	500 Server error	Service unavailable	UnavailableService	503 Service Unavailable	Error Description	Error Code	Http Status Code	Server should be shutdown	MustShutdownServer	400 bad request	Invalid parts ID	InvalidPartsID	400 bad request	Parts was removed before	PartsRemovedBefore	400 bad request	Invalid parts type	InvalidPartsType	400 bad request	Disk was detached before	DiskDetachedBefore	400 bad request	Incorrect server ID	InvalidServerID	400 bad request	Fail to detach drive	FailDetachDrive	400 bad request	Server was suspended before	VMSuspended	403 forbidden	Server is locked by other procedure	VMLocked	403 forbidden
Error Description	Error Code	Http Status Code																																																													
Expired signature	ExpiredSig	412 bad Request																																																													
Invalid headers	InvalidHeader	412 bad Request																																																													
Incorrect Locale code passing	InvalidLocale	400 Bad Request																																																													
No such member	NotExistMem	412 bad Request																																																													
Fail Authentication	FailAuth	415 Forbidden																																																													
Account problem or suspended	ACPrb	403 Forbidden																																																													
Unsupported REST action	NoRestMethod	415 not allowed method																																																													
Server unexpected error	UnexpectedError	500 Server error																																																													
Service unavailable	UnavailableService	503 Service Unavailable																																																													
Error Description	Error Code	Http Status Code																																																													
Server should be shutdown	MustShutdownServer	400 bad request																																																													
Invalid parts ID	InvalidPartsID	400 bad request																																																													
Parts was removed before	PartsRemovedBefore	400 bad request																																																													
Invalid parts type	InvalidPartsType	400 bad request																																																													
Disk was detached before	DiskDetachedBefore	400 bad request																																																													
Incorrect server ID	InvalidServerID	400 bad request																																																													
Fail to detach drive	FailDetachDrive	400 bad request																																																													
Server was suspended before	VMSuspended	403 forbidden																																																													
Server is locked by other procedure	VMLocked	403 forbidden																																																													



<b>REST Request Header</b>	DELETE / HTTP/1.1 Host: a.cserver.mygrid.asia Content-Length: 0 Date: Mon, 03 Mar 2008 12:00:00 +0800 <i>(or passing x-pan-date instead of Date)</i> Authorization: 112122334214:dsfdksfjdklsfjkldsfj-dsfd= <i>(access_id : signature)</i>
<b>Returned XML</b>	<?xml version="1.0" encoding="UTF-8" ?> <<CloudServerAPI> <Status>SUCCESS</Status> </CloudServerAPI>

## Error Handling

In Aspen Cloud, it returns the error in XML format and takes advantages of http status code.

Besides, Aspen Cloud Server API also returns the error in XML format. If you require more details about your failure call, you can refer to the XML content.

The XML error message can be English, Traditional Chinese and Simplified Chinese due to user request. All unrecognized error will be shown in English.

Following are the sample returned XML format.

### http header sample :

```
Date: Mon, 03 Mar 2008 06:08:42 GMT
Content-Type: application/xml
Content-Length: 112
Connection: close
```

### XML Body sample :

```
<Error>
  <ErrorCode>FailAuth</ErrorCode>
  <ErrorMessage>Fail to authentication</ErrorMessage>
  <HttpStatusCode>400</HttpStatusCode>
  (The http status code also be shown in XML)
</Error>
```

**Error Code Table**

Error Description	Error Code	Http Status Code	Related Functions
Expired signature	ExpiredSig	400 Bad Request	All APIs
Invalid headers	InvalidHeader	400 Bad Request	All APIs
Incorrect Locale code passing	InvalidLocale	400 Bad Request	All APIs
No such member	NotExistMem	400 Bad Request	All APIs
No such Cloud Server	NoSuchVM	400 Bad Request	ID 3 – 7, 16
Invalid IDC code	InvalidIDCCode	400 bad request	ID 8, 13, 14, 15, 16
Invalid Template Code	InvalidTemplateCode	400 bad request	ID 8, 14
Invalid Plan Code	InvalidPlanCode	400 bad request	ID 8
Invalid Zone Code	InvalidZoneCode	400 bad request	ID 8
Insufficient balance to subscribe	InsufficientBalance	400 bad request	ID 8, 16
Over the maximum subscription server number.	OverMaxSubscribedServers	400 bad request	ID 8
Incorrect starting date	InvalidBillingStartDate	400 bad request	ID 10
Incorrect ending date	InvalidBillingEndDate	400 bad request	ID 10
Incorrect starting offset	InvalidStartingOffset	400 bad request	ID 10
Incorrect maximum record number	InvalidMaxRecordReturn	400 bad request	ID 10
Incorrect city code	InvalidCityCode	400 bad request	ID 12
No administration right	NoAdminAccessRight	400 bad request	ID 8
Invalid server ID you provided	InvalidServerID	400 bad request	ID 8, 15, 16, 18, 19, 20
No IDC approval	NoApproval	400 bad request	ID 8
No such service	NoSuchService	400 bad request	ID 12, 15, 16, 17, 18
Invalid parts	InvalidParts	400 bad request	ID 16, 18
Should shutdown server	MustShutdownServer	400 bad request	ID 16, 18, 19, 20
Over max allowed CPU no.	ExceedMaxCPU	400 bad request	ID 16
Over max allowed RAM size	ExceedMaxRAM	400 bad request	ID 16
Over max allowed connect drive no.	ExceedMaxDriveNo	400 bad request	ID 16, 19
Fail to adjust CPU	FailAdjustCPUNumber	400 bad request	ID 16, 18
Fail to adjust RAM size	FailAdjustRAMSize	400 bad request	ID 16, 18
Fail to add hard drive	FailAddDrive	400 bad request	ID 16
Fail to remove hard drive	FailRemoveDrive	400 bad request	ID 18
Parts was removed before	PartsRemovedBefore	400 bad request	ID 18, 19, 20
Parts type incorrect	InvalidPartsType	400 bad request	ID 18, 19, 20
Parts ID incorrect	InvalidPartsID	400 bad request	ID 19, 20



### Cloud Server API – Development Guideline

Disk drive was attached before	DiskAttachedBefore	400 bad request	ID 19
Fail to attach drive	FailAttachDrive	400 bad request	ID 19
Disk drive was detached before	DiskDetachedBefore	400 bad request	ID 20
Fail to detach drive	FailDetachDrive	400 bad request	ID 20
Fail Authentication	FailAuth	403 Forbidden	All APIs
Account problem or suspended	ACPrb	403 Forbidden	All APIs
The cloud server is locked by other process.	VMLocked	403 Forbidden	ID 3 – 7, 16, 18, 19, 20
The cloud server was suspended.	VMSuspended	403 Forbidden	ID 3 – 7, 16, 18, 19, 20
Unsupported REST action	NoRestMethod	405 Not allowed method	All APIs
Server unexpected error	UnexpectedError	500 Server error	All APIs
Fail to terminate in server side.	FailTerminateVM	500 Server error r	ID 9
Service unavailable	UnavailableService	503 Service Unavailable	All APIs